FLAMMABLE STORAGE CABINETS

- Double-wall 18-gauge welded steel construction with 1 1/2" air space
- Dual 2" capped vents with flash arrestors
- Full-height piano hinges open a full 180° for easy access
- Locking handle with 3-point latch
- 2" high leak proof door sill
 All shelves are adjustable on 2 1/2" centers
- Adjustable leveling feet
- Tough corrosive resistant finish
- Manual-close doors automatically self-latch
- Meets NFPA Code 30 and OSHA standard 1910 106 for storage for Class I, II and III liquids
- FM approved









Order	Door	Capacity	Adjustable	Exterior Dimensions			ns	Wt.	
No.	Туре	Gallons	Shelves	W"	Х	D"	X	H"	lbs.
SEE911	Single	12	1	23	Х	18	Х	35	99
SEE912	Single	16	1	23	Х	18	X	44	116
SEE913	Double	22	1	35	Х	22	X	35	151
SEE914	Double	24	3	43	Х	12	Х	44	173
SAQ325	Double	30	1	43	Х	18	Х	44	174
SAQ326	Double	45	2	43	Х	18	Х	65	252
SAS521	Double	60	2	34	Х	34	Х	65	430
	_								

O7 100E 1	Double	00	_	0 i X	0 i x	00	100
EXTRA SHEL	.F						
Order				Dimens	ions		Wt.
No.		For use with		W" x	D"		lbs.
SEE922		SEE911, SEE912		19 1/2 x	14		5
SEE923		SEE913		31 1/2 x	18		9
SEE924		SEE914		39 1/2 x	8		6
SAQ328		SAQ325, SAQ326		39 3/8 x	14		9
CACE74		SASE21		30.3/8 ^	30		12

AN INFORMED CHOICE IS ALWAYS THE BEST CHOICE

CONSIDER THE FOLLOWING WHEN MAKING THE SELECTION THAT IS JUST RIGHT FOR YOU:

- 1. Type of chemical being stored
- 2. Applicable regulations
- Capacity needed
- 4. Type of container being stored
- 5. Door and handle style preference
- 6. Warning label system
- 7. Performance testing (3rd party approvals)



APPLICABLE REGULATIONS & APPROVALS

THIRD PARTY TESTING IS YOUR ASSURANCE OF PERFORMANCE.





CODE COMPLIANCE:

Federal, provincial and local regulations may apply. Contact your local fire department for guidance.

OSHA 29 CFR 1910.106 / NFPA Code 30 Section 4.3.3

CONVENIENCE & PROTECTION FACTORS

DOOR STYLE PREFERENCE:

Whereas door style is usually chosen by preference, the Uniform Fire Code (UFC) mandates the use of self-closing cabinets. Cabinets with self-closing and self-latching doors provide an extra measure of protection.



MANUAL

Economical manual close doors permit doors to open a full 180°. When pushed closed they will automatically self-latch.



SLIDING

A single bi-fold, sliding door glides smoothly on a spring loaded track for easy, one handed access to cabinet contents. It self-latches and self-closes, and is equipped with a fusible link to hold the door open during use and melts at 165°F (74°C) to automatically close door under fire conditions.

point closure with keyed lock and our exclusive self-latching mechanism on all door styles.



SELF-CLOSE

This style self-indexes. self-latches and self-closes to automatically shut doors upon release. Mechanism is concealed in the top wall, maximizing available shelf space. Fusible links hold doors open during use. In the event of a fire, fusible links will melt at 165°F (74°C) to automatically close doors. All Justrite® cabinet doors feature a continuous piano hinge for smooth operation, a three-

TYPE OF CHEMICAL TO BE STORED:

Using colour and labelling in your storage practices helps identify, organise and segregate liquids. It also helps fire department personnel recognise hazards when responding to fire situations.

CAPACITY NEEDS:

A wide variety of code compliant Justrite® cabinets are available in sizes ranging from 4 gallons US (15 litres) to 120 gallons US (454 litres). Smaller cabinets allow solvents to be stored at worksite locations saving costly trips to a central storage room. Undercounter, wall mount and compact style cabinets add to safe storage, even when space is at a premium. For high capacity storage, larger sized cabinets designed specifically to house 30 gallon US (114 litres) or 55 gallon US (208 litres) US drums are available.

PERFORMANCE TESTING:

Justrite® cabinets are third party tested by Factory Mutual Research and/ or Underwriters Laboratories and built to OSHA/NFPA standards.

A SELF-LATCHING **CABINET MAKES** A DIFFERENCE!

A self-latching door and handle is critical as it does not require the user to manually rotate a handle to ensure the three-point latch is properly engaged. This is an important detail since an unlatched cabinet leaves the flammable contents exposed to a potential fire, where every single second of protection counts. A safety cabinet must be latched for it to perform according to code, providing maximum safety under fire conditions. A stainless steel bullet latching system offers optimum longevity with increased heat resistance.

DOOR HANDLE:

SURE-GRIP® U-LOC™ HANDLE

Attractive, self-latching paddle style handle offers easy fingertip access to contents. Flush-mounted design keeps aisles clear and reduces dangerous "catches" from passing traffic. Exclusive padlock tag offers added security. Padlock serves as a visual deterrent and provides the flexibility of the lock being master keyed, keyed alike or keyed different for convenience.



HAZ-ALERT™ SYSTEM

When illuminated with a flashlight, hazardous warning labels burst with high visibility under fire conditions or power outages. Labels are strategically positioned in high and low zones to help firefighters easily locate volatile liquids.





SURE-GRIP® EX FLAMMABLE STORAGE CABINETS

- Double wall welded 18-gauge steel construction with 1 1/2" of insulating air space
- 3-point stainless steel bullet latches offer longevity and increased heat resistance
- U-Loc[™] handle keeps aisles clear and offers fingertip access; comes with 2 keys or accepts optional padlock for greater security
- Two flame arrester vents and ground wire connection screw
- 2" deep leakproof sill
- Adjustable leveler legs, and galvanized SpillSlope™ shelves that adjust on 3" centres
- ullet Haz-Alert $^{\text{TM}}$ reflective warning labels
- Durable yellow powder coat paint finish provides long life and exceptional chemical resistance
- Meet NFPA and OSHA requirements

W JUSTRITE®

FM approved





SAP509

Order No.	Mfg. No.	Door Type	Capacity Gallons	Adjustable Shelves	Ext. Dim. W" x D"x H"	Wt. Ibs.
SAP509	893000	2 Doors, Manual	30	1	43 x 18 x 44	231
SAQ020	893080	Sliding Door, Self-Closing	30	1	43 x 18 x 44	246
SAQ021	893020	2 Doors, Self-Closing	30	1	43 x 18 x 44	237
SAP510	894500	2 Doors, Manual	45	2	43 x 18 x 65	310
SAQ022	894580	Sliding Door, Self-Closing	45	2	43 x 18 x 65	330
SAQ023	894520	2 Doors, Self-Closing	45	2	43 x 18 x 65	313
SAQ024	896000	2 Doors, Manual	60	2	34 x 34 x 65	387
SAQ025	896020	2 Doors, Self-Closing	60	2	34 x 34 x 65	392
SAQ026*	899000	2 Doors, Manual	90	2	43 x 34 x 65	480
SAQ027*	899020	2 Doors, Self-Closing	90	2	43 x 34 x 65	480

ACCESSORIES

Order No.	Mfg. No.	Description	Dimensions"	Wt. lbs.
SAP839	29937	Extra Shelf for 30 and 45-Gallon cabinets	-	9
SAQ028	29944	Extra Shelf for 60-Gallon cabinets	-	14
SAQ029	29945	Extra Shelf for 90-Gallon cabinets	-	18
SAK285	25987	Cabinet Cover for 30 and 45-Gallon Cabinets	8 1/2 x 42 1/2 x 18	26
SAK286	25989	Cabinet Cover for 60-Gallon Cabinets	16 x 33 1/2 x 34	42
SAR311	84000	Seismic Bracket Kit	47	7
SAR312	84002	Cabinet Riser Frame for Forklift or Pallet Jack	18 x 43	45
SAR313	84001	Rolling Cart for 30-Gallon Cabinets	18 x 43	49

^{*} Codes state that not more than 60 gallons may be Class I and Class II liquids.

INSULATED FLAMMABLE STORAGE CABINETS

- Double wall welded 18-gauge steel construction, filled with 2" of fire-proof insulation
- Two manual close doors
- Full length piano-hinged doors with three-point lock on door
- Two 2" flame arrester vents and ground wire connection screw
- 2" deep leak-proof sill, adjustable galvanized shelves on 1/2" centres
- Zinc-plated leveler legs
- Safety yellow
- ULC approved



Order No.	Mfg. No.	Door Type		Adjust. Shelves	W"		. Di D"			Wt. lbs.
2" FIBR	E INSUI	LATED								
SA087	WB30	2 Door, Manua	I 30	1	44	х	19	х	45	350
SA088	WB45	2 Door, Manua	45	2	44	Х	19	Х	66	430

٩C	CE	SS	O	RIES	

Order	Mfg.		Wt.
No.	No.	Description	lbs.
SA086	WB-S	Extra Shelf for SA087 & SA088	9
DA623	LE74	Insulated Grounding Wire w/C-Clamp and Clip	1
DA622	LE62	Flexible Bonding Wire w/Two Clips	1
DA621	LE61	Flexible Bonding Wire w/C-Clamp and Clip	1









SURE-GRIP® EX HIGH SECURITY FLAMMABLE SAFETY CABINETS

- The same durable constructon as Justrite®'s regular Sure-Grip® cabinet with added layers of security
- Safely store and protect costly fuels or chemicals from tampering or theft
- Security system includes 1/4" x 2" steel bar stock,
- a high visibility barrier bar secured across both doors
- Crossbar is firmly supported by two brackets welded across the front of the cabinet doors and interlocks onto two sidewall brackets
- Padlock lugs on crossbar and side bar channel provide double layered steel strength and accept 2 x No. 5 Master Lock® keyed-alike (SR867, sold separately)
- Lockable doors with Sure-Grip® handle with a three-point latch
- FM approved



Maintenance & Industrial



Support brackets are firmly welded to cabinet door for extra tamper resistance.



Contrasting crossbar can be completely removed from the cabinet when not in use.







Order	Mfg.		Capacity	Adjustable	Ext. Dim.					Wt.	
No.	No.	Door Type	Gallons	Shelves	V	٧"	X	D"	X	H"	lbs.
SAN604	SC29883Y	2 Doors, Self-Close, Yellow	30	1	4	3	х	18	Х	44	235
SAN606	SC29883R	2 Doors, Self-Close, Red	30	1	4	3	х	18	Х	44	235
SAN578	29884Y	2 Doors, Manual, Yellow	45	2	4	3	х	18	Х	65	310
SAN605	SC29884Y	2 Doors, Self-Close, Yellow	45	2	4	3	Х	18	Х	65	313
SAN580	29884R	2 Doors, Manual, Red	45	2	4	3	Х	18	Х	65	310
SAN607	SC29884R	2 Doors, Self-Close, Red	45	2	4	3	Х	18	Х	65	313

SURE-GRIP® EX AEROSOL CAN BENCHTOP CABINETS

STORE AEROSOLS SAFELY!

- · Fits virtually anywhere
- Double-wall, 18-gauge welded steel with 1 1/2" of insulating air space
- 24-gauge galvanized steel roll-out shelves with stop-guard protection
- Two fixed position shelves have twelve 2 3/4" dia. openings and accept cans up to 10" tall
- Shelves are removable for easy cleaning
- U-Loc[™] handle comes with double key set or accepts optional padlock for greater security
- Haz-Alert^{†M} reflective warning labels
- Durable yellow powder coat paint finish inside and out
- Meets NFPA and OSHA regulations





Order Mfg.				Ext. Dim.	Wt.
No.	No.	Door Type	Capacity	W" x D" x H"	lbs.
SAQ045	890500	1 Door, Manual	24 Aerosol Cans	21 x 18 x 27	100



SURE-GRIP® EX SPECIALTY CABINETS

STORE SMALLER QUANTITIES NEARBY!



When storing smaller quantities of flammable liquids at a work station or adding to existing storage capacities, specialty cabinets make it possible to store flammables safely even when available space is at a minimum. These cabinets offer U-LocTM handles and come with a double key set or accept an optional padlock for greater security. Chemical resistant powder coat paint resists corrosion for years of service. They also have Haz-AlertTM reflective warning labels to offer visibility under dark conditions. Meet NFPA and OSHA regulations.

WALL MOUNT SAFETY CABINETS

- Store small containers without taking up extra floor space
- Mounts easily with furnished brackets



UNDERCOUNTER SAFETY CABINETS

· Designed to fit under most counters

• Designed with a kick plate

to match existing casework

SAQ040

SLIMLINE SAFETY CABINETS

 Small footprint allows placement almost anywhere



SAQ033

COUNTERTOP & COMPAC SAFETY CABINETS

- Improved access to often used liquids, without compromising safety
- Portable size keeps work areas flexible



SAQ035

STACKABLE PIGGYBACK CABINETS

- Can be used singly or stacked to provide expanded or segregated storage
- Suitable for wall mounting or countertop



SAQ031

MINI SAFETY CABINETS

- Offers the smallest footprint
- Hold small quantities of flammables for cleaning and maintenance at point-of-use
- Three bungee cords keep contents in place during transportation on service vehicles or carts



Order	Mfg.	Cabinet	Door	Capacity	Adjustable		E	xt. Di	m.		Listing	Wt.
No.	No.	Туре	Туре	Gallons	Shelves	W"	X	D"	X	H"	/Approvals	lbs.
SEG862	890200	Mini	1 Door, Manual	Aerosols	1	17	Х	8	Х	22	-	43
SAQ034	890400	Countertop	1 Door, Manual	4	1	17	Х	17	Х	22	-	62
SAQ030*	891300	Piggyback	2 Doors, Manual	12	-	43	Χ	18	Х	18	FM	129
SAQ036	891200	Compac	1 Door, Manual	12	1	23 1/4	Х	18	Х	35	FM	129
SAQ037	891220	Compac	1 Door, Self-Closing	12	1	23 1/4	Х	18	Х	35	FM	131
SAQ031*	891700	Piggyback	2 Doors, Manual	17	1	43	Х	18	Х	24	FM	157
SAQ040	893400	Wall Mount	2 Doors, Manual	20	5	43	Х	12	Х	44	FM	221
SAQ041	892300	Undercounter	2 Doors, Manual	22	1	35	Χ	2	Х	35	FM	190
SAQ032	892200	Slimline	1 Door, Manual	22	3	23	Χ	18	Х	65	FM	200
SAQ033	892220	Slimline	1 Door, Self-Close	22	3	23	Х	18	Х	65	FM	200

EXTRA SHELVES

SAQ041

Order No.	Mfg. No.	Description	Wt. Ibs.
		F	
SAQ043	29936	12 and 15-Gallon Compac Cabinets	5
SAQ044	29939	22-Gallon Undercounter Cabinets	12

^{*}Piggyback cabinets are not to be used with sliding door cabinets.

DRUM STORAGE SURE-GRIP® EX SAFETY CABINETS

Suitable for storage of larger quantities of flammable liquids and have all the same features as Justrite®'s standard safety cabinets.

SURE-GRIP® EX VERTICAL DRUM STORAGE CABINETS

- Safely store one or two 30 to 55-gallon US drums
- Half-depth shelf allows additional storage of Class III flammables
- · Accommodates drums equipped with pumps or funnels so cabinet can be used for waste accumulation or as a pumping station
- Rollers at bottom of cabinet facilitate drum movement (sold separately)
- · Ramp for drum cabinets (sold separately) aids in loading drums with a hand truck

SURE-GRIP® EX HORIZONTAL DRUM STORAGE CABINETS

- Designed to house drums being used for gravity flow dispensing
- · Interior provides room for a drip can and includes tracks to guide a cradle into position, drum cradle not included

SURE-GRIP® EX DOUBLE-DUTY SAFETY CABINETS

- Combines vertical drum and safety storage into one partitioned cabinet
- Safely stores up to twelve 5-gallon US safety cans on the left side, and one vertical 30 or 55-gallon US drum on the right side
- · Both compartments have an independently self-latching, locking door for maximum protection under fire conditions







SAQ052



Order	Mfg.		Drum	Ext. Dim.	Listing	Wt.
No.	No.	Door Type	US Cap.	W" x D" x H"	/Approvals	lbs.
YELLOW	VERTICAL D	RUM STORAGE CABINETS				_
SAQ046	896260	2 Doors, Manual	1-55 gallons	34 x 34 x 65	FM	425
SAQ047	896270	2 Doors, Self-Close	1-55 gallons	34 x 34 x 65	FM	425
SAQ048	899160	2 Doors, Manual	2-55 gallons	59 x 34 x 65	-	781
SAQ049	899060	2 Doors, Manual	2-30 gallons	43 x 34 x 65	FM	495
SAQ050	899070	2 Doors, Self-Close	2-30 gallons	43 x 34 x 65	FM	495
YELLOW	HORIZONTA	L DRUM STORAGE CABINETS				
SAQ051	899300	2 Doors, Manual	1-55 gallons	30 x 48 x 50	-	371
SAQ052	899320	2 Doors, Self-Close	1-55 gallons	30 x 48 x 50	-	371
YELLOW	DOUBLE-DU	ITY SAFETY CABINETS				
SAQ053	899260	2 Doors, Manual	1-55 gallons	59 x 34 x 65	-	700
SAQ054	899270	2 Doors, External Self-Close	1-55 gallons	59 x 34 x 65	-	700
ACCESSO	ORIES	Description				Wt. lbs.
SAI480	25932	Drum Ramp for all Justrite® Drum Cabinets	-	-	-	28
SAK286	25989	Cabinet Cover for SAQ046 and SAQ047	-	-	-	100
SEE311	25920	Drum Rollers for Single Drum Vertical Cabinets	-	-	-	52
SEE312	25922	Drum Rollers for Double Drum Vertical Cabinets	-	-	-	99

HAZARDOUS WASTE SAFETY CABINETS

- For temporary on-site accumulation and storage of waste liquids
- All-welded 18-gauge double wall construction with 1 1/2" air space
- 2" leakproof sill and 2" flame arrester vents
- One galvanized steel, half-depth shelf adjustable on 2 1/4" centres
- U-Loc[™] handle comes with double key set or accepts optional padlock for greater security
- Rollers (sold separately) at bottom of cabinet facilitate drum movement
- All models have two doors
- Haz-Alert[™] reflective warning labels
- Meets OSHA and NFPA regulations
- FM approved



Order	Mfg.		Drum	Ext. Dim.	Wt.
No.	No.	Door Type	Capacity	W" x D" x H"	lbs.
SAQ073	8962053	Manual	1-55 gallon	34 x 34 x 65	405
SAQ074	8962253	Self-Closing	1-55 gallon	34 x 34 x 65	406
SAQ075	8991053	Manual	2-55 gallon	59 x 34 x 65	615
ACCESSO	RIES	Description		L" x W"	Wt. lbs.
SEE311	25920	Drum Rollers for	Single Cabinet	29 1/2 x 30	52
SEE312	259220	Drum Rollers for	Double Cabinet	55 1/2 x 30	99



SAQ075

DRUM SAFETY CABINETS

Choice of 2" fibre insulated or 1 1/2" air insulated cabinets.

VERTICAL CABINETS:

- Keeps drum close to work area to safely contain and dispense flammable liquids
- Shelf can be added should faucet allow for enough clearance
- · Capacity: 45 imperial gallons
- Includes drum support

HORIZONTAL CABINETS:

- Stores one 55-gallon drum and drum cradle (sold separately)
- Ground cables are recommended when transferring liquids
- Ideal for easy dispensing of flammable liquids

Order	Mfg.		No. of	[Dim	ens	ion	s	Wt.
No.	No.	Insulation	Shelves	W"	X	D"	X	H"	lbs.
VERTICA	L CABINETS								
SA090	WB55V	2" Fibre	1	35	Х	35	Х	63	470
SA069	FM45V	1 1/2" Air	1	35	Х	35	Х	63	420
HORIZOI	NTAL CABINET	rs							
SA089	WB45H	2" Fibre	-	35	Х	50	Х	50	500
SA068	FM45H	1 1/2" Air	-	35	Х	50	Х	50	384
ACCESS	ORIES	Descripti	on						
DA591	45R	Drum Ro	cker, Rigid Ca	sters					35
SAJ102	WB-S60	Extra Sh	elf for SA090	and SA	069)			17
DA623	LE74	Insulated	Grounding W	/ire w/C	C-CI	amp	ar	nd Clip	1
DA622	LE62	Flexible I	Bonding Wire	w/Two	Cli	ps ·			1
DA621	LE61	Flexible I	Bonding Wire	w/C-Cla	ami	o an	d C	lip	1



SA090

SOLID POLYETHYLENE ACID CABINETS

- Sturdy solid-wall chemically resistant polyethylene construction with sealed sump
- · Suitable for highly aggressive liquids
- 3-point door latch on undercounter and stand alone models offers secure closure and vapour control
- Adjustable shelf on undercounter and stand alone models adjusts on 3" centres
- External 2" NPT vent/exhaust connections
- Pad lockable hasps
- · Levelling feet on all 4 corners
- HazAlert[™] reflective warning labels



Order	Mfg.		No. of	2.5-L bottle			Ext. Di	m.		Wt.
No.	No.	Style	Doors	Capacity	W"	X	D"	X	Н"	lbs.
SEB217	24004	Countertop	1	6	17	Х	17	Х	22	26
SEB218	24010	Undercounter	2	36	36	х	21 3/4	Х	35 3/4	160
SEB219	24015	Stand Alone	2	36	36	Х	21 3/4	Х	35 3/4	160



SEB219

SEB217

SE386

POLYETHYLENE ACID CABINETS

One-piece molded body for maximum chemical resistance and leak protection. Both units can be padlocked to prevent unauthorized access.

COUNTERTOP ACID CABINET

- · Spill tray inside the cabinet is removable for easy cleaning
- Includes a handy work tray stored under cabinet
- Door can be hinged from either side

ACID CABINET

- Two adjustable shelves and storage in doors for small containers
- Removable sumps for easy cleaning
- Two compartments allow segregation of non-compatible corrosives
- Two vent holes on the back of cabinet; one at the bottom left and one at the top right
- Cabinet top doubles as a handy workspace
- Cabinet is sized to fit under counter or free standing and can be secured to wall for stability







Order	Mfg.		Bottles	Ext. Dim.	Wt.
No.	No.	Door Type	Capacity	W" x D" x H"	lbs.
SE385	24040	1 Door, Manual	2-4 litre	14 1/4 x 16 1/4 x 19 3/	4 30
SE386	24160	2 Doors, Manual	30-1 litre	36 x 23 1/2 x 35	120

SURE-GRIP® EX ACID/CORROSIVE STORAGE CABINETS

Built to the same standards as Justrite®'s flammable storage cabinets with the addition of poly tray liners and a specially formulated epoxy, powder coat paint.

- Poly liners on shelves and poly sump liner are removable for easy cleaning
- 30-gallon cabinet is also equipped with a polycabinet-top work tray
- U-Loc[™] handle offers easy fingertip access and accepts optional padlock
- Undercounter model has a 3 1/2" H x 2 1/2" D kick plate to mount flush with other cabinetry
- Haz-Alert™ reflective warning labels
- Meets NFPA and OSHA regulations
- FM approved

Note: Not to be used with phenol, nitric and sulfuric acids.











Order No.	Mfg. No.	Door Type	Capacity Gallons	Adjustable Shelves	Ext. Dim. W" x D"x H"	Wt. Ibs.
SAQ055	892302	2 Doors, Manual, Undercounter	22	1	35 x 22 x 35	210
SAQ056	892202	1 Door, Manual, Slimline	22	3	23 x 18 x 65	200
SAQ057	893002	2 Doors, Manual	30	1	43 x 18 x 44	233
SAQ058	893082	Sliding Door, Self-Closing	30	1	43 x 18 x 44	250
SAQ059	893022	2 Doors, Self-Closing	30	1	43 x 18 x 44	242
SAQ060	894502	2 Doors, Manual	45	2	43 x 18 x 65	316
SAQ061	894542	Sliding Door, Self-Closing	45	2	43 x 18 x 65	335
SAQ062	894522	2 Doors, Self-Closing	45	2	43 x 18 x 65	317
ACCESSOF	RIES	Description				Wt. Ibs.
SAQ044	29939	Extra Shelf for 22-Gallon Cabinets	-			10
SAQ063	29965	Poly Tray for 22-Gallon Cabinets				6
SAP839	29937	Extra Shelf for 30 and 45-Gallon Cabine	ets			8
SAQ064	29962	Poly Tray for 30 and 45-Gallon Cabinets				22

CHEMCOR® LINED ACID/CORROSIVE CABINETS

Unique, flame-coated ChemCor® thermoplastic liner is applied to Justrite®'s acid/corrosive safety cabinets for unsurpassed corrosion protection and fire protection.

- 100% seamless liner on all interior walls, ceiling, sump, inside doors and shelves protects exposed cabinet surfaces without gaps
- Seam-free surface eliminates the need for rivets or fasteners which risk corrosion from seep-through chemicals
- U-Loc[™] handle comes with double key set or accepts optional padlock for greater security
- Haz-AlertTM reflective warning labels
- Durable, thermoplastic non-porous interior coating resists staining and cleans-up easily
- Maximum protection from harsh acids and corrosive chemicals plus fire protection and code compliance in a wide variety of double-wall steel safety cabinets
- FM approved



SAQ067

Seamless Liner

- 2	Backed by our	
18	10 Vaar	
100	iu rear	
ā	Limited Warranty	

Order No.	Mfg. No.	Door Type	Capacity Gallons	Adjustable Shelves	Ext. Dim. W" x D"x H"	Wt. lbs.
SAQ065	8923022	2 Doors, Manual, Undercounter	22	1	35 x 22 x 35	210
SAQ066	8922022	1 Door, Manual, Slimline	22	3	23 x 18 x 65	200
SAQ067	8930022	2 Doors, Manual	30	1	43 x 18 x 44	233
SAQ068	8930822	Sliding Door, Self-Closing	30	1	43 x 18 x 44	250
SAQ069	8930222	2 Doors, Self-Closing	30	1	43 x 18 x 44	242
SAQ070	8945022	2 Doors, Manual	45	2	43 x 18 x 65	316
SAQ071	8945822	Sliding Door, Self-Closing	45	2	43 x 18 x 65	335
SAQ072	8945222	2 Doors, Self-Closing	45	2	43 x 18 x 65	317

PAINT & INK STORAGE CABINETS

- Double-wall 18-gauge welded steel construction with 1 1/2" insulating air space
- Dual 2" capped vents with flash arresters
- Full-height piano hinges open a full 180° for easy access
- · Locking handle with 3-point latch
- 2" high leak proof door sill
- All shelves are adjustable on 2 1/2" centres
- Adjustable levelling feet
- Tough corrosive-resistant finish
- Meets NFPA Code 30 and OSHA standard 1910 106 for storage Class I, II and III liquids
- FM approved



Cabinet vent w/flame arrester



Locking handle for greater security








Order		Capacity	Adjustable		Е	xt. Di	m.		Wt.
No.	Door Type	Gallons	Shelves	W"	х	D"	х	H"	lbs.
SAQ327	2-Door, Manual	60	5	43	х	18	Х	65	267
ACCESSORIES									
Order					Din	nensi	ons"		Wt.
No.	Description	n		W"	'	Х	D	"	lbs.
SAQ328	Extra Shelf	f for 60-Gallon Cabinet	i	39 3	/8	Х	14	1	9

SURE-GRIP® EX PAINT & INK SAFETY STORAGE CABINETS

Separate and identify Class III combustibles in high performance paint and ink safety storage cabinets. They have the same safety and quality features and options that are available in Justrite®'s safety cabinets for flammables with additional shelves.

• Multiple shelves are ideal for 1-gallon paint cans (Class III liquids)

- Cabinets are available in 20, 40, 60 and 120-gallon capacities
- U-Loc[™] handle comes with double key set or accepts optional padlock for greater security
- Haz-AlertTM reflective warning labels
- Durable red powder coat paint finish easily identifies contents and is highly chemical resistant
- Meets NFPA and OSHA regulations
- FM approved





SAR311 Seismic bracket kit secures cabinet to wall







Order	Mfg.		Capacity	Adjustable	Ext. D	im		Wt.
No.	No.	Door Type	Gallons	Shelves	W" x D"	х	H"	lbs.
SAQ079	891511	1 Door, Manual, Compac	20	2	23 1/4 x 18	Х	44	154
SAQ080	891531	1 Door, Self-Closing, Compac	20	2	23 1/4 x 18	Х	44	157
SAQ081	893011	2 Doors, Manual	40	3	43 x 18	Х	44	239
SAQ082	893081	Sliding Door, Self-Closing	40	3	43 x 18	Х	44	260
SAQ083	893031	2 Doors, Self-Closing	40	3	43 x 18	Х	44	254
SAQ084	894511	2 Doors, Manual	60	5	43 x 18	Х	65	345
SAQ085	894581	Sliding Door, Self-Closing	60	5	43 x 18	Х	65	330
SAQ086	894531	2 Doors, Self-Closing	60	5	43 x 18	Х	65	361
SAQ087*	896011	2 Doors, Manual	96	5	34 x 34	X	65	424
SAQ088*	896031	2 Doors, Self-Closing	96	5	34 x 34	X	65	434

ACCESSORIES

Order No.	Mfg. No.	Description	Dimensions"	Wt. lbs.
SAP839	29937	Extra Shelf for 40-Gallon Cabinets	-	8
SAQ028	29944	Extra Shelf for 60-Gallon Cabinets	-	14
SAR311	84000	Seismic Bracket Kit	47	7
SAR313	84001	Rolling Cart for 40-Gallon Cabinet	18 x 43	49

^{*}Codes state that not more than 60 gallons may be Class I and Class II liquids.

DOCUMENT STORAGE BOXES

ACCESSIBLE STORAGE & PROTECTION

 Weather resistant, no metal parts to corrode - keeps papers clean and dry in dusty, harsh environments

High density polyethylene is durable, rustproof and easy to clean

- Mounts on cabinets, machinery, equipment or walls for fast, easy access to information at point of use
- · Lock holes on medium and large units accept padlock or zip ties
- Four built-in mounting holes on medium and large sized units provide added mounting options
- Designated area to add your own labels or optional label pack available
- · Also handy for portable document storage
- High visibility red colour
- Keeps MSDS documents for compliance with OSHA 29 CFR 1910.1200
- Optional label pack includes 4 yellow labels (2 blank and 2 printed - MSDS and instruction manual, sold separately)

Includes heavy-duty tape for drill-free mounting





Use nearly anywhere! 4 sizes - 3 styles



Order	Mfg.		Int. Dim. (approx)	Ext. Dim.	Gasketed	Lock
No.	No.	Description	W" x D" x H"	W" x D" x H"	Closure	Hole Dia."
SAN581	23303	Medium Top Opening	8 3/4 x 1 5/8 x 11 1/2	10 1/4 x 2 1/4 x 12 1/2	No	1/4
SAN582	23304	Medium Front Opening	8 5/8 x 1 x 12 1/4	11 x 2 1/8 x 14 1/2	Yes	3/8
SAN584	23306	Large Front Opening	10 3/4 x 2 1/4 x 13 1/4	13 1/8 x 3 9/16 x 15 3/4	Yes	3/8
SAN585	23310	Label Pack - 4 Yellow Label	ls: 2 Blank and 2 Printed - MSD	S and Instruction Manual	-	-
SAN583	23305	Tube, Twist-On Lid	12 x 3 dia.	12.5 x 3.7 dia.	Yes	-

EMERGENCY PREPAREDNESS STORAGE CABINETS

- For protected, quick access to emergency supplies during a disaster
- Features a fire resistant design with durable powder paint "emergency orange" finish
- GloAlert[™] glow-in-the-dark labels ensure fast location during power outages
- Spacious design includes four adjustable shelves
- High quality 3-point stainless steel bullet latching system
- Smooth opening/closing piano hinge doors
- U-Loc[™] handle comes with 2 keys or accepts optional padlock for greater security
- Four adjustable leveling feet
- PowerPort™ SEG861 has an installed electrical pass-through connection and comes with an external 9' power cord and 10 A rates, 6-outlet power strip with 38" cord for charging walkie talkies, flashlights, etc. inside the cabinet
- Design tested in accordance with ASTM and NFPA time temperature curves





Order	Mfg.	Adjustable						Wt.
No.	No.	Shelves	W"	X	D"	X	H"	lbs.
SEG860	860001	4	43	Х	18	Х	63	315
SEG861	860002	4	43	Х	18	Х	63	315



VAPORTRAP™ FILTERS

- Stainless steel wire mesh cartridge containing activated carbon, absorbs volatile organic compound (VOC's) vapours
- Improve your work environment by reducing employees inhalation exposure to harmful VOC's and lowering emissions of VOC's into the atmosphere
- Cylindrical design allows 360° airflow for maximum surface contact
- High strength magnets offer flexible placement/ repositioning anywhere within the cabinet
- Date notation area on label serves as a reminder for replacement; life cycle varies based upon vapour types and concentrations
- Contains two filters per package

Order No. SEG859 Mfg. No. 29916







DRUMLOC™ SAFETY LOCKERS

- A compliant, non-fire rated safety locker for the storage of hazardous chemicals
- Continuously welded heavy gauge steel construction
- Secondary spill containment leakproof all-welded sump
- Steel grate flooring
- 54" wide steel door system with 3-point lock hardware
- Natural draft ventilation
- 15-year structural warranty
- FM approved
- Meets EPA and OSHA requirements

W JUSTRITE®

Order No.	Mfg. No.	Ext. Dim. L' x W' x H'	Sump Depth"	Sump Cap. Gal.	Max No. of Drums	Wt. Ibs.
SEJ789	DL2	5 x 3.5 x 6.33	8	62.7	2	1248
SEJ790	DL4	5 x 5 x 6.33	6	71.5	4	1644
SEJ791	DL6	7 x 5 x 8.33	6	104.3	6	2214
SEJ792	DL9	7 x 7 x 8.33	6	152	9	2737
SEJ793	DL12	9 x 7 x 8.33	6	199.7	12	3260
SEJ794	DL16	10 x 10 x 8.33	6	329	16	4481



♠ ♠ W JUSTRITE®

TYPE II ACCUFLOW™ SAFETY CANS

- $\bullet \ \, \mathsf{AccuFlow}^{\mathsf{TM}} \ \, \mathsf{exclusive} \ \, \mathsf{Safe}\text{-}\mathsf{Squeeze}^{\scriptscriptstyle (\!g\!)} \ \, \mathsf{trigger} \ \, \mathsf{mechanism}$ allows for smooth flow and accurate pouring
- Auto-venting pressure relief cap
- · Leak proof self-closing gasketed lid controls vapours and spills
- · Long lasting stainless steel flame arrester dissipates heat and prevents flashback ignition
- Extra large ID zone reduces misuse and has warning in three languages
- FM approved, UL/ULC listed
- 10-year limited warranty







Red	Mfg.	Yellow	Mfg.	Blue	Mfg.	Green	Mfg.	Capacity	E	xt. Dim	
Order No.	No.	US Gal.	Dia."	x	H"						
5/8" HOSE	WIDTH										
SEA217	7210120	SEA218	7210220	SEA219	7210320	SEA220	7210420	1	9 1/2	Х	11
SEA221	7220120	SEA222	7220220	SEA253	7220320	SEA223	7220420	2	9 1/2	Х	13 1/2
SEA224	7225120	SEA226	7225220	SEA228	7225320	SEA230	7225420	2.5	11 1/2	Х	12
SEA232	7250120	SEA234	7250220	SEA236	7250320	SEA238	7250420	5	11 1/2	Х	18
1" HOSE W	IDTH										
SEA225	7225130	SEA227	7225230	SEA229	7225330	SEA231	7225430	2.5	11 1/2	х	12
SEA233	7250130	SEA235	7250230	SEA237	7250330	SEA239	7250430	5	11 1/2	Х	18

TYPE I SAFETY CANS

- Compliant Type I safety cans are designed with a single spout for filling and pouring of all types of flammable liquids
- High performance, chemical resistant stainless steel flame arrester that stops flashback ignition, provides faster liquid flow, and offers exceptional durability and corrosion protection for long life
- Self-venting, self-closing leak tight lid prevents ruptures from pressure build-up and controls vapours and spills
- Unique counterbalance design with full-fisted grip handle offers gravity-assisted pouring
- Warning label includes large ID zone for user labelling to avoid misuse, reduce the potential for incompatible mixtures, or may be used to designate department or individual owner
- Optional poly funnel offers targeted pouring
- Finished in a tough powder coat paint, Justrite® cans resist chemicals and stand up to heavy abuse
- FM approved, UL/ULC listed
- 10-year limited warranty







Red	Mfg.	Yellow	Mfg.	Blue	Mfg.	Green	Mfg.		Ex	t. D	im.
Order No.	No.	Order No.	No.	Order No.	No.	Order No.	No.	Capacity	Dia."	Х	H"
WITH FUNI	NEL										
SEA240	7110110	SEA241	7110210	SEA242	7110310	SEA243	7110410	1 US Gal.	9 1/2	Х	11
SEA204	7120110	SEA244	7120210	SEA245	7120310	SEA246	7120410	2 US Gal.	9 1/2	Х	13 3/4
SEA208	7125110	SEA247	7125210	SEA248	7125310	SEA249	7125410	2.5 US Gal.	11 3/4	Х	11 1/2
SEA213	7150110	SEA250	7150210	SEA251	7150310	SEA252	7150410	5 US Gal.	11 3/4	Х	16 7/8
WITHOUT	FUNNEL										
SAI516	10001	-	-	-	-	-	-	1 Pint	4 5/8	Х	6 3/4
SAI517	10101	-	-	-	-	-	-	1 Quart	4 5/8	Х	8 1/4
SEA199	7110100	SEA200	7110200	SEA201	7110300	SEA202	7110400	1 US Gal.	9 1/2	Х	11
SEA203	7120100	SEA205	7120200	SEA206	7120300	SEB084	7120400	2 US Gal.	9 1/2	Х	13 3/
SEA207	7125100	SEA209	7125200	SEA210	7125300	SEA211	7125400	2.5 US Gal.	11 3/4	Х	11 1/2
SEA212	7150100	SEA214	7150200	SEA215	7150300	SEA216	7150400	5 US Gal.	11 3/4	Х	16 7/8

RFPI	ACEME	NT FI	INNEL
NEFL	ACLIVIE	.141 F	JININEL

ILLI LAGLIVILIA	IIOIVIVEE	
Order No.	Mfg. No.	Description
SAJ675	11202Y	I'm Easy funnel spout in polypropylene






D.O.T. ACCUFLOW™ SAFETY CANS

- Hold-down bracket with easy-to-grip tightening screw prevents vapour release and spills during transport
- Easy-to-engage fusible link bracket melts at 165°F (75°C) to prevent dangerous pressure build-up
- AccuFlow's[™] exclusive Safe-Squeeze[®] trigger mechanism allows for smooth flow and accurate pouring
- Leak-tight, self-closing lid automatically vests between 3 and 5 PSIG
- Heavy roll bars protect the spout
- D.O.T. compliant and FM approved









10 Year

LABORATORY SAFETY CANS

- Convenient dispensing in two styles for use on shelves or in tilt stands
- · Self-closing faucets offer controlled dispensing of hazardous liquids
- Fill spouts have self-closing pressure relief caps with built-in vacuum breakers and double mesh flame arresters
- The lab faucet allows easier dispensing into containers with small openings
- Capacity: 5 US gallons
- FM approved



Order No.	Mfg. No.	Description	Faucet
		•	
SEC080	7150140	Steel Shelf Can	Control Flow Lab, 3/4" Brass
SEC081	7150150	Steel Plate Shelf Can	3/4" NPT Rigid Brass
SEC082	7150146	Steel Plate Tilt Can w/Stand	Control Flow Lab, 3/4" Brass
SEC083	7150156	Steel Plate Tilt Can w/Stand	3/4" NPT Rigid Brass
SEC084	14545	Polyethylene Shelf Can	Control Flow Lab, 3/4" Brass
SEC085	14535	Polyethylene Tilt Can w/Stand	Control Flow Lab, 3/4" Brass



TYPE I & TYPE II STEEL SAFETY CANS

- Feature a spring loaded lid with an internal flame arrester
- Made of 24-gauge terne plate steel
- Type I cans feature a single pour spout and a spring-loaded handle
- Type II cans feature separate fill and flexible pour spout with a hose for pouring accuracy
- FM approved complies with OSHA standards



Order	Mfg.	Capa	city	Hose	e Di	m.	Ca	n Di	im.	Wt.
No.	No.	US Gal.	Litres	Dia."	X	L"	Dia."	X	Н"	lbs.
TYPE I										
SA145	WB100	1	3.8	-	-	-	8 1/2	Х	12 1/8	5
SA146	WB101	1 IMP	4.6	-	-	-	8 1/8	Х	13 1/8	6
SA147	WB102	2	7.6	-	-	-	8 1/2	Х	16 1/8	6
SA148	WB103	3	11.4	-	-	-	11 1/2	Х	15 1/8	8
SA149	WB105	5	18.9	-	-	-	11 1/2	Х	19 1/2	9
SA150	WB106	5 IMP	22.7	-	-	-	11 1/2	Х	21 1/2	10
TYPE II										
SA151	WB200	1	3.8	5/8	Х	6	8 1/2	х	12	6
SA152	WB201	1 IMP	4.6	5/8	Х	6	8 1/8	Х	13 1/2	7
SA153	WB202	2	7.6	5/8	Х	6	8 1/2	Х	16 1/8	10
SA154	WB203	3	11.4	1	Х	12	11 1/2	Х	16	10
SA155	WB205	5	18.9	1	Х	12	11 1/2	Х	20	12
SA156	WB206	5 IMP	22.7	1	х	12	11 1/2	Х	21 1/2	12



REPLACE	MENT SPOU	T FOR TYPE II CANS
Order	Mfg.	Dimensions
No.	No.	Dia." x L"
SA157	R-3409	5/8 x 9

TYPE I POLYETHYLENE SAFETY CANS

Choose Type I non-metallic safety cans when dent and chemical resistance are important. Constructed of high-density polyethylene offering distinct advantages over steel units.

- Dent, chip and puncture-resistant polyethylene stands up to harsh corrosives
- Current carrying carbon insert grounds the opening and flame arrester
- Self-close spout and pressure relief mechanism
- Flame arrester prevents ignition sources from entering the can
- Stainless steel hardware provides chemical protection
- FM approved



Order	Mfg.	Capacity		D	imensio	ns	
No.	No.	US Gallons	L"	X	W"	X	H"
FM APPRO	OVED - OVA	L					
SC291	14160	1	7 5/8	Х	4 5/8	Х	12 3/4

Order	Mfg.	Capacity	Dim	ensi	ons
No.	No.	US Gallons	Outer Dia."	X	H"
FM, UL,	ULC APPROV	ED - ROUND			
SC293	14261	2 1/2	10 3/4	Х	14 1/4
SC295	14561	5	12 3/4	Х	16



SC291

POLYETHYLENE LIQUID DISPOSAL CANS

- High density polyethylene cans contain corrosives and flammable liquids better than conventional metal cans
- Large opening for better control when disposing of liquids
- Fixed position handle allows lid to stay open for easier pouring
- Flame arrester guards against outside sources
- When closed, the cap automatically vents between 3 and 5 PSIG
- Stainless steel hardware provides chemical protection
- FM approved



W JUSTRITE®

Order	Mfg.	Capacity	Dimensions			
No.	No.	US Gal.	Outer Dia."	X	H"	
SC306	14762	2	12	Х	14 3/4	
SC308	14765	5	12	Х	20	

QUICK-DISCONNECT SAFETY DISPOSAL CANS

- Collect waste liquid easily and safely with FM approved quick-disconnect safety disposal cans
- Ideal for HPLC applications
- Safeguard against spills and accidents associated with common collection practices
- Stainless steel fittings with Teflon® O-rings for chemical resistance or economically priced polypropylene fittings



SAI570



Solvents flow freely into can through 3/8" tubing and can is easily disconnected with a special valved fitting without vapour release or solvent leakage.



Order	Mfg.	Mfg. Fitting		Dimensions			
No.	No.	Material	Outer Dia. "	X	Н"	Material	
2 US GA	ALLON CA						
SAI569	PP12752	Polypropylene	12	Х	14 3/4	EPDM	
SAI570	TF12752	Stainless Steel	12	Χ	14 3/4	Teflon®	
5 US G	ALLON CA	PACITY					
SAI571	PP12755	Polypropylene	12	Х	20	EPDM	
SAI572	TF12755	Stainless Steel	12	Х	20	Teflon®	

Safety Cans

DISPENSER BOTTLES

Dispense flammable liquids and solvents safely without waste or exposure.

- · Small size allows for easy, one-handed dispensing of liquids directly onto work surface
- Brass dispenser valves are leak proof and self-closing
- · Minimises spills and waste
- Bottle design is textured for firm gripping

Mfg.

No.

14002

14004

14010

Order

SC311

SA131 SA133

No.

• FM approved for flammables



. 1	
Dimensions	Listing

Н"

5 1/2

x 5 1/2

x 10 1/2

Х

/Approval

FΜ

FM

7
70 A

DISPENSING SQUEEZE BOTTLES

Allow safe dispensing of liquid small components or sub-assemblies with a minimum of over-spray. Squeezing the bottle produces a fine stream of liquid.

 Low-density polyethylene with stainless steel wire that allows stem to be shaped to reach "hard to get at" areas





Order	Mfg.	Capacity	Dimensions
No. No.	OZ.	Outer Dia." x H"	
SA132	14009	16	3 x 7 1/2
SA134	14011	32	3 1/2 x 9 1/8

ECO® GAS CANS

• The safest, most environmentally-friendly cans available

Outer Dia." x

2 1/4

3 1/8

4

• Uses patented DuPont® Laminar Technology resulting in a permeation level well below the CARB required rate of 0.40 grams/gallon/day

Capacity

4 Oz.

8 Oz.

1 Quart

- · Equipped with self-venting spout that automatically shuts off when gas tank is full
- · Rustproof, unbreakable and non-corroding
- ULC and CSA approved





Order No.	Mfg. No.	Colour	Capacity US Gal.	Capacity Litres	
SAO954 07450		Red	1 1/4	5	
SAO955	07378	Red	2 1/2	10	
SAK866	05096	Red	5	18.8	

REPLACEMENT PARTS					
Order No.	Mfg. No.	Description			
SAK867	05459	Eco® spout			

JERRY CANS

- Made from high-density polyethylene
- · Lightweight, crushproof design with extra headspace built in to accommodate expansion
- User-friendly "easy pour" design, self-venting spouts and child resistant closures
- · Cans are rustproof, unbreakable and non-corroding
- 5 US gallon available in two colours; red for gasoline and yellow for diesel
- Self-venting Eco® spout (SAK867, sold separately) automatically shuts off when the gas tank is full
- SAK857 is a combo can, gasoline and oil
- ULC and CSA approved



Order No.	Mfg. No.	•		Capacity US Gallons	Capacity Litres
SAP356	07081	Red	Gasoline	1 1/4	5
SAP357	07079	Red	Gasoline	2 1/2	10
SAO958	07622	Red	Gasoline	5.3	20
SAK856	03609	Red	Gasoline	5.3	20
SAK857	03615	Red (Combo)	Gasoline/Oil	1 1/2 & 2 3/4 Qts	6 & 2.5
SAP399	07649	Yellow	Diesel	5.3	20

REPLACEMENT PARTS

Order No.	Mfg. No.	Description
SAS111	03583	Black Cap, Yellow Stopper and Vent Cap
SAS112	03647	Black Cap, Yellow Stopper, Spout and Vent Cap
SAK867	05459	Eco® Spout



FLO N' GO™ SUPERFLO™ COMBO JERRY CANS

- Fuel siphon pumps gas in any direction for easy, clean fill-ups in hard-to-reach fuel tanks
- Siphon comes with a 10-L (2.5 gal.) fuel can
- At-the-handle pump control allows for auto shut-off and restarts, as well as clean, hassle-free siphon control
- Delivers a flow rate of 1 GPM (3.7 L/min) when in siphon mode
- Child safety lock included
- Ideal for smaller engines including lawnmowers, trimmers, chainsaws, generators, blowers, edgers, snow throwers, or any small engine that requires refuelling

Order No. SAR369 Mfg. No. 06921



Scepter SYMBOL OF QUALITY

STOP FLOW SAFETY SPOUTS

- Convenient, easy-to-use spout that reduces the amount of fuel spills
- Push down to engage the spout to pour and lift to close the spout when finished

Order No. SAR373 Mfg. No. SFPS



WATER CONTAINERS

- 20-L (5.3 Gal.) capacity
- Polyethylene
- Crushproof
- Rustproof

Order No. SAR372 Mfg. No. W520







FLO N' GO™ DURAMAX™ FUEL CONTAINERS

- Large, portable fuel container on wheels designed for industrial, commercial, and recreational applications
- High density polyethylene resistant to corrosion and denting
- Sturdy 6" wheels and extra-deep patented gas pump handle allows you to eliminate spillage and overfills
- Flow rate of 2 GPM in siphon mode
- Two shut-off valves make it safe and easy to disconnect the pump for refilling and transportation
- Includes: 14 Gal. (53-L) fuel container with the patented Flo n' go Maxflo™ siphon/pump and 10' (3 m) hose

Order No. SAR302 Mfg. No. 06792





FLO N' GO™ MAXFLO™ COMBO JERRY CANS

- Siphon pumps gas in any direction for easy, clean fill-ups in hard-to-reach fuel tanks
- At-the-handle pump control allows for auto shut-off and restarts, as well as clean, hassle-free siphon control
- Delivers a flow rate of over 2 GPM (7.5 L/min) when used in siphon mode
- · Child safety lock included
- Ideal for larger applications including lawn tractors, boat engines, Jet Skis/ PWC, ATVs, snowmobiles, farm equipment, pressure washers, snow throwers, and light commercial equipment





Order No.	Mfg. No.	Description
SAR370	06922	Combo w/ 25 L (6.6-Gallon Capacity) Can
SAR371	06799	Siphon Only

MINI BENCH-TOP OILY WASTE CANS

- Small footprint is convenient in confined work areas
- Constructed of durable galvanized steel
- Easily accommodates counter top applications
- Specially designed SoundGard™ lid significantly reduces lid closure noise
- Fire resistant design makes it ideal for disposing of hazardous waste materials like swabs or wipes that contain flammable solvents, adhesives, or cleaning agents
- Compact height easily accepts standard long cotton-tip applicators used for cleaning parts
- Lid opens to a maximum 60° and is self closing to minimize the chance of fire caused by spontaneous combustion
- · Chemically resistant red powder coat paint finish for extended service life
- Leak-proof 0.45-gallon (1.7-L) capacity container
- Reusable, will not rust or puncture
- · Fire tested and FM and OSHA approved

Order	Mfg.	Dimensions Wt.				
No.	No.	Dia.*	Х	Н	lbs.	
SAS238	09410	4 5/8" Base	Х	6 1/2"	2	









Safety Cans

OILY WASTE CANS

OSHA compliant oily waste cans are essential whenever solvent cloths and wiping rags are used.

- Self-closing cover reduces oxygen source to prevent fire from starting
- Round construction and raised bottom encourage air circulation to disperse heat and prevent rust
- · Rugged galvanised steel body in a variety of sizes accommodate any work area
- Carrying handle for portability
- 6 21 US Gal. foot-operated models are FM approved and UL listed
- 2 US gallon hand-operated, countertop model is FM approved







JUSTRITE® 10 Year



SoundGard [™] Silver Order No.	Mfg. No.	Yellow Order No.	Mfg. No.	Red Order No.	Mfg. No.	Cap US Gal.	Dimensi Outer Dia." x	ons H"	Wt. lbs.
0.00.110.						20 04			
-	-	SR361	09200Y	SR356	09200	2	9 5/8 x	9 1/8	О
SAR304	09104	SR362	09101	SR357	09100	6	11 7/8 x	15 7/8	10
SAR305	09304	SR363	09301	SR358	09300	10	13 15/16 x	18 1/4	12
SAR306	09504	SR364	09501	SR359	09500	14	16 1/16 x	20 1/4	15
SAR307	09704	SR365	09701	SR360	09700	21	18 3/8 x	23 7/16	22

DRIP CANS

- Ideal for placement below drum faucets, drain or valves to catch drips or overflows of liquids
- Perforated metal fire baffle acts as a flame arrester to protect contents from fire exposure
- Catches up to one US gallon of liquid
- Top removes for quick cleaning
- Made of 24-gauge coated steel with a durable powder paint finish
- · Easily portable with handy side handles
- 9 3/8" OD x 4 1/2" H
- · Weight: 3 lbs.
- FM approved

Order No. SAH514 Mfg. No. 10376



JUSTRITE"

FUSIBLE LINK SELF-CLOSING DRUM COVERS

- Convert open top 55 US gallon steel drums into fire-safe receptacles for combustible trash
- Replaceable fusible link assembly inside the cover melts at 160°F, automatically slamming the cover shut if a fire occurs in the drum
- Steel construction
- Solvent resistant, red baked-on enamel finish
- Fits drums from 22 1/2" to 22 3/4" in diameter
- Weight: 16 lbs.
- FM approved.

Order No. DA097 Mfg. No. 26750





PLUNGER CANS

- Dispense flammable liquids and solvents safely onto cloths or swabs without waste or exposure
- Plunger fills upper pan for soaking
- · Surplus liquid drains safely back into can
- Brass pump parts resist corrosion
- Steel and polyethylene cans available
- FM approved







Order	Mfg.			Dimensions	
No.	No.	Description	Capacity	Outer Dia.'	'x H"
SA129	10008	Steel Plunger Can	1 Pint	4 7/8	x 6
SA130	10108	Steel Plunger Can	1 Quart	7 1/4	x 6 1/2
SC309	10308	Steel Plunger Can	1 US Gallor	n 7 1/4	x 11
SC310	14018	Polyethylene	1 Quart	5 1/2	x 9
		Plunger Can			