#### ERGONOMIC FLOORING VS. ERGONOMIC MATTING


#### ERGONOMIC FLOORING

Ergonomic flooring covers a larger area than standard work station mats and is available for work areas subject to moisture and oily substances. Ergonomic flooring also comes in various solidity levels to accommodate different weight requirements for applications and equipment. Harder flooring can be used when working with heavy materials, thereby allowing employees to use transport devices such as carts and dollies. This reduces heavy lifting and strenuous physical activity. In addition, ergonomic flooring reduces the risk of serious bodily injury due to its inherently softer surface.

Ergonomic flooring comes in various sizes using what Wearwell® calls a "Positive Lock". This refers to a seamless installation that stays intact unless you "unzip" the components. Also, different colours are available to match the look of your work environment. No fasteners or adhesives are used. You simply interconnect the tiles according to your floor plan. Materials can be trimmed and cut to respect the angles of walls, equipment and traffic areas.

Maintenance is simple because tiles can easily be replaced without having to remove giant sections of the flooring. However, not all modular matting can be used for ergonomic flooring. Wearwell® describes the concept of the "Three P's" in regards to installation:

- "Positive" locking: These are the only products used. They make for snug seams and do not move around unless taken apart intentionally.
- "Permanent" locking: These require adhesives, heat bonding or mechanical fasteners, making repair and reconfiguration very difficult.
- "Passive" locking: These have connectors that overlay each other but do not tightly lock together




#### **ERGONOMIC MATTING**

Used primarily for work stations and assembly line applications, ergonomic matting is typically a turnkey solution that comes in a variety of materials for application issues such as:

- Comfort
- Slip prevention
- Static discharge
- Weld sparks
- Contamination control
- Flame risk

Because ergonomic matting comes in so many shapes and materials, employees have considerable choices to satisfy their desired comfort level in their respective work areas. The different surfaces available include diamond plate, marbleized tile-top, corrugated and pebbled.

Ergonomic matting is usually ready right out of the box and does not require additional preparation. Some products are available in rolls and can be customized in shape, length and width beforehand, so you do not need to make on-the-spot modifications in the workspace.





FREQUENTLY ASKED QUESTIONS:

Simply remove it and

on the ramp.

replace with a new tile.

of the tile that has interlocks?

Simply cut off the interlocks

What if one of my tiles gets damaged?

How do you connect a ramp to the side

What do I need to install ErgoDeck®?

A rubber mallet. Each box of tiles

contains installation instructions.

### ERGODECK® ERGONOMIC FLOORING SYSTEMS NO. 560 & NO. 562

- Professional grade 18" x 18" super-sized ergonomic tiles quickly assemble to cover large and custom-sized areas
- The patented LockSafe® system securely connects the tiles for a neat, clean, installation that will withstand heavy use and cart traffic
- The incredibly substantial design creates a floor above the facility floor, covering up imperfections and safety hazards
- ErgoDeck® tiles can be unlocked and repositioned to create a different configuration when work flow changes
- Optional 6" wide safety ramps and corners accommodate carts and have countersunk holes so ErgoDeck® can be attached to the floor
- 7/8" thick
- Designed specifically for heavy cart traffic with load capacity of 64 PSI
- · Available in open grid and solid tile designs

# WARRANTY

#### **ERGODECK® HEAVY-DUTY OPEN GRID NO. 560**


• For use in wet (non-greasy) or dry areas where small debris or fluids are present

#### **ERGODECK® HEAVY-DUTY SOLID NO. 562**

• For use in dry areas where small parts fall to the floor, or where ease of maintenance is a priority


| Order                     |                                 |    |   | Dim. |   |    | Qty   |
|---------------------------|---------------------------------|----|---|------|---|----|-------|
| No.                       | Description                     | W" | X | L"   | X | D" | /Case |
| SAL215                    | Open Grid No. 560, Single Tile  | 18 | Х | 18   |   | -  | 10    |
| SAL224                    | Solid No. 562, Single Tile      | 18 | Χ | 18   |   | -  | 10    |
| RAMP & CORNER ACCESSORIES |                                 |    |   |      |   |    |       |
| SAL219                    | Ramp - Yellow, Single           | 6  | Х | 18   |   | -  | 10    |
| SAL217                    | Outside Corner - Yellow, Single | 6  | Х | 15   | Х | 15 | 4     |

## **WEARWELL**



### ERGODECK® GENERAL PURPOSE NO. 564 & NO. 566

- General purpose version of the original ErgoDeck® specifically designed to increase worker productivity
- Combination of 68 durometer compound and Flex-points on the underside provides flexibility underfoot
- Professional grade 18" x 18" super-sized ergonomic tiles quickly assemble to cover large and custom-sized areas
- Patented LockSafe® system securely connects the tiles for a neat installation to withstand heavy use and cart traffic
- · Tiles can be unlocked and repositioned to create different configurations
- Optional 6" wide safety ramps and corners
- 7/8" thick
- · Colour: Charcoal



## **WEARWELL**

3-YEAR WARRANTY

| Order                     |                                 | I  | Dim | ١. | Qty   |
|---------------------------|---------------------------------|----|-----|----|-------|
| No.                       | Description                     | W" | X   | L" | /Case |
| SAQ312                    | Open Grid No. 564, Case         | 18 | Х   | 18 | 10    |
| SAQ313                    | Solid No. 566, Case             | 18 | Х   | 18 | 10    |
| RAMP & CORNER ACCESSORIES |                                 |    |     |    |       |
| SAQ314                    | Ramp - Charcoal, Case           | 6  | Х   | 18 | 10    |
| SAQ315                    | Outside Corner - Charcoal, Case | 15 | Х   | 15 |       |
| SAL219                    | Ramp - Yellow, Case             | 6  | Х   | 18 | 10    |
| SAL217                    | Outside Corner - Yellow, Case   | 15 | Х   | 15 | 4     |

## ERGODECK® W/INTEGRATED NO-SLIP CLEATS NO. 552 & NO. 553

- This non-slip flooring is engineered to deliver exceptional traction in even the most extreme environments
- The patented LockSafe® positive interlocking system delivers secure connections but can be unlocked as needed for replacement or repositioning
- The optional 6" side safety ramps and corners have countersunk holes for semi-permanent installation
- Unmatched slip prevention
- Customize in 3" increments to fit any area or configuration
- Can withstand power-washing and aggressive maintenance
- 100% silicone-free PVC tiles provide maximum durability
- 18" x18" tiles
- Open grid: Recommend usage in wet or dry areas where small debris or fluids are present
- Solid: Recommend usage in dry areas





## **WEARWELL**

Description

Open Grid No.

Open Grid No. Solid No. 552,

Solid No. 552, Case

Order No.

**SEI922** 

**SEI923** 

**SEI924** 

**SEI925** 


|                  |    | Dim | Qty |       |
|------------------|----|-----|-----|-------|
|                  | w" |     | L"  | /Case |
| 553, Single Tile | 18 | Х   | 18  | -     |
| 553, Case        | 18 | Х   | 18  | 10    |
| Single Tile      | 18 | х   | 18  | -     |

# 18 x 18 10

3-YEAR WARRANTY

### REJUVENATOR® NO. 501 & NO. 502

- 100% urethane anti-fatigue mats provide long term value
- A great combination of comfort, performance and exceptional resilience, this mat is literally crush resistant
- Tear and abrasion resistant, these mats are exceptional in dry, heavy use areas
- Reiuvenator® Connect No. 502 3' x 3' mats connect on all sides with optional 2" wide bevels to increase safety
- Thickness: 5/8"





| Order                |    | Dim. |    | Wt.  |  |
|----------------------|----|------|----|------|--|
| No.                  | W' | x    | L' | lbs. |  |
| REJUVENATOR® NO. 501 |    |      |    |      |  |
| NH597                | 2  | х    | 3  | 9    |  |
| NH598                | 3  | X    | 5  | 21   |  |







#### **WEARWELL**

| Order    |                      |    | Dim. |     |  |
|----------|----------------------|----|------|-----|--|
| No.      | Description          | W  | х    | L   |  |
| REJUVENA | TOR® CONNECT NO. 502 |    |      |     |  |
| SAR340   | Mat                  | 3' | х    | 3'  |  |
| EDGE     |                      |    |      |     |  |
| SAR341   | Female, Black        | 2" | х    | 39" |  |
| SAR342   | Male, Black          | 2" | Х    | 39" |  |
| SAR345   | Female, Yellow       | 2" | Х    | 39" |  |
| SAR346   | Male, Yellow         | 2" | Х    | 39" |  |

#### 24/SEVEN® COMFORTABLE, MODULAR, SIMPLE TO USE

- The 3' x 3' mats also interlock on all four sides to cover large areas, or can be used as single stations
- Optional yellow and black borders provide safe access

WHAT IS YOUR APPLICATION? CHOOSE FROM 5 FORMULATIONS

General purpose rubber - Natural rubber formulation designed for general application, such as areas with water or debris

CFR rubber - Designed for areas with mineral oil based cutting fluids and solvents


CFR rubber with GritWorks!® - For wet areas that need extra traction

NBR 100% nitrile - Designed for areas with petrochemicals


such as hydrocarbons, naphthenes, paraffins and petroleum distillates

NBR 100% nitrile with GritWorks!® - For wet areas that need extra traction

#### WITH DRAINAGE







3" x 39" Female (F) Ramp snaps onto the protruding mat knobs

#### **REASONS TO CHOOSE 24/SEVEN®**

- Modular design
- · Quick installation and replacement
- Comfort
- Five formulations
- Can customize on site



## **\$\$\$** WEARWELL

| Order  |   |    | Dim. |    |
|--------|---|----|------|----|
| No.    | Description                             | W' | х    | L' |
| SOLID  |   |    |      |    |
| NH589  | General Purpose No. 570 Solid Mat       | 3  | Х    | 3  |
| SAQ100 | CFR No. 570 Solid Mat                   | 3  | Х    | 3  |
| SAL233 | CFR w/Gritworks!® No. 574 Solid Mat     | 3  | Х    | 3  |
| SAQ101 | Nitrile No. 570 Solid Mat               | 3  | Х    | 3  |
| SAQ103 | Nitrile w/Gritworks!® No. 574 Solid Mat | 3  | Х    | 3  |
| OPEN   |   |    |      |    |
| NH587  | General Purpose No. 572 Open Mat        | 3  | Х    | 3  |
| SAL228 | CFR No. 572 Open Mat                    | 3  | Х    | 3  |
| SAL234 | CFR w/Gritworks!® No. 576 Open Mat      | 3  | Х    | 3  |
| SAQ102 | Nitrile No. 572 Open Mat                | 3  | Х    | 3  |
| SAQ104 | Nitrile w/Gritworks!® No. 576 Open Mat  | 3  | Х    | 3  |

| Order        |                        | Dim. |   |    |  |
|--------------|------------------------|------|---|----|--|
| No.          | Description            | W"   | Х | L" |  |
| BLACK RAMPS  |                        |      |   |    |  |
| NH591        | General Purpose Female | 3    | Х | 39 |  |
| NH594        | General Purpose Male   | 3    | Х | 39 |  |
| SAQ128       | CFR Female             | 3    | Х | 39 |  |
| SAQ125       | CFR Male               | 3    | Х | 39 |  |
| SAQ129       | Nitrile Female         | 3    | Х | 39 |  |
| SAQ126       | Nitrile Male           | 3    | Х | 39 |  |
| YELLOW RAMPS |                        |      |   |    |  |
| NH593        | General Purpose Female | 3    | Х | 39 |  |
| NH596        | General Purpose Male   | 3    | Х | 39 |  |
| SAL230       | CFR Female             | 3    | Х | 39 |  |
| SAL232       | CFR Male               | 3    | Х | 39 |  |
| SAQ130       | Nitrile Female         | 3    | Х | 39 |  |
| SAQ127       | Nitrile Male           | 3    | Х | 39 |  |

### DIAMOND-PLATE SPONGECOTE® NO. 414 & NO. 415

- Our Diamond-Plate products define the market for dry area anti-fatigue matting
- These mats have a Nitricell® sponge base, a unique and resilient nitrile rubber composite that provides unparalleled comfort, resilience and long-term performance
- Designed for optimised worker productivity in heavy-use production and lab areas, the PVC diamond-plate surface resists abrasion and most chemical spills
- Edges safety bevelled
- Available in two distinct versions:

#### **ULTRASOFT DIAMOND-PLATE NO. 414**

Ultimate Performance has a double-thick Nitricell® sponge base for a little extra comfort

#### **DIAMOND-PLATE SPONGECOTE NO. 415**

Best Performance is a standard 9/16" thick and has been a best seller for over 20 years!

#### **SSWEARWELL**







Double thick Nitricell® sponge base



Black w/

Yellow Borders

9/16'

Nitricell® sponge base


| NO. 414             |      |   |    |      |  |  |
|---------------------|------|---|----|------|--|--|
| Order               | Dim. |   |    | Wt.  |  |  |
| No.                 | W'   | X | L' | lbs. |  |  |
| 15/16" BLACK/YELLOW |      |   |    |      |  |  |
| <b>SAJ810</b>       | 2    | Х | 3  | 9    |  |  |
| NG924               | 3    | Х | 5  | 21   |  |  |
| NG925               | 2    | Х | 75 | 225  |  |  |
| NG926               | 3    | Х | 75 | 338  |  |  |
| NG927               | 4    | Х | 75 | 450  |  |  |
| 15/16" E            | BLAC | K |    |      |  |  |
| <b>SAJ809</b>       | 2    | Х | 3  | 9    |  |  |
| NG917               | 3    | Х | 5  | 21   |  |  |
| NG918               | 2    | Х | 75 | 225  |  |  |
| NG919               | 3    | Х | 75 | 338  |  |  |
| NG920               | 4    | Х | 75 | 450  |  |  |

| Order              | - 1 | Dim |    | Wt.  |  |  |
|--------------------|-----|-----|----|------|--|--|
| No.                | W'  | X   | L' | lbs. |  |  |
| 9/16" BLACK/YELLOW |     |     |    |      |  |  |
| NB416              | 2   | Х   | 3  | 8    |  |  |
| NB430              | 3   | Х   | 5  | 18   |  |  |
| NB425              | 2   | Х   | 75 | 166  |  |  |
| NB439              | 3   | Х   | 75 | 244  |  |  |
| SAL165             | 4   | Х   | 75 | 340  |  |  |
| 9/16" Bl           | ACK | (   |    |      |  |  |
| NB420              | 2   | Х   | 3  | 8    |  |  |
| NB431              | 3   | Х   | 5  | 18   |  |  |
| NB426              | 2   | Х   | 75 | 166  |  |  |
| NB440              | 3   | Х   | 75 | 244  |  |  |
| <b>SAL164</b>      | 4   | Х   | 75 | 340  |  |  |

Available in cuts up to 75' in length

## SMART DIAMOND-PLATE NO. 497

- An economical and green solution for preventing worker fatigue
- Diamond plate surface with a 100% recycled urethane composite sponge base
- Comfortable and functional in dry industrial applications
- · Black and black with yellow border
- Green rating > 80% recycled







## **\$\$\$** WEARWELL

| Order         | Dim.         | Order Dim.                 |  |
|---------------|--------------|----------------------------|--|
| No.           | W' x L'      | No. W'x L'                 |  |
| 1" BLACK      | (            | 5/8" BLACK                 |  |
| <b>SBA878</b> | 2 x 3        | <b>SBA894</b> 2 x 3        |  |
| SBA879        | 3 x 5        | <b>SBA895</b> 3 x 5        |  |
| SBA880        | 2 x 75       | <b>SBA896</b> 2 x 75       |  |
| <b>SBA881</b> | 3 x 75       | <b>SBA897</b> 3 x 75       |  |
| <b>SBA882</b> | 4 x 75       | <b>SBA898</b> 4 x 75       |  |
| <b>SBA883</b> | 2 x lin.ft.* | <b>SBA899</b> 2 x lin.ft.* |  |
| SBA884        | 3 x lin.ft.* | <b>SBA900</b> 3 x lin.ft.* |  |
| 1" BLACK      | ( W/YELLOW   | 5/8" BLACK W/YELLOW        |  |
| SBA886        | 2 x 3        | <b>SBA902</b> 2 x 3        |  |
| <b>SBA887</b> | 3 x 5        | <b>SBA903</b> 3 x 5        |  |
| SBA888        | 2 x 75       | <b>SBA904</b> 2 x 75       |  |
| <b>SBA889</b> | 3 x 75       | <b>SBA905</b> 3 x 75       |  |
| SBA890        | 4 x 75       | <b>SBA906</b> 4 x 75       |  |
| SBA891        | 2 x lin.ft.* | <b>SBA907</b> 2 x lin.ft.* |  |
| SBA892        | 3 x lin.ft.* | <b>SBA908</b> 3 x lin.ft.* |  |

\*Cuts up to 75' in length

## DIAMOND-PLATE SELECT NO. 495

- An excellent anti-fatigue mat designed to increase comfort and relieve stress; it's popular in dry industrial, lab and commercial applications
- The specially formulated, PVC Flex-Link<sup>™</sup> sponge base is compounded for enhanced functionality
- Available in two thicknesses:
   Standard: Overall thickness 9/16"
   Ultra thick: Overall thickness 15/16"
- Green rating > 50% post consumer material
- Colours: Black with yellow borders





| Order        |      | Wt.   |       |           |
|--------------|------|-------|-------|-----------|
| No.          | W'   | X     | L'    | lbs.      |
| 9/16"        |      |       |       |           |
| SAL349       | 2    | х     | 3     | 8         |
| SAL358       | 3    | Х     | 5     | 18        |
| SAL361       | 3    | Х     | 75    | 244       |
| 15/16"       |      |       |       |           |
| SAL201       | 2    | Х     | 3     | 9         |
| SAL207       | 3    | Х     | 5     | 21        |
| SAL209       | 3    | Х     | 75    | 338       |
| Available in | cuts | up to | o 75' | in length |



### TILE-TOP AM NO. 420

- 100% anti-microbial (AM)
- Non-porous vinyl surface is constructed with an extra wear layer for exceptional abrasion and chemical resistance

• Micropure sponge base made with nitrile rubber composite offers exceptional comfort, resilience and anti-microbial properties

- 1/2" thick
- · For use in laboratories, pharmacies, healthcare facilities, pharmaceutical manufacturing and even packaging and postal areas



| Black | Blue | Gre |
|-------|------|-----|
| .==   |      |     |
|       |      |     |

| Grey | Charco |
|------|--------|
|      |        |

## **WEARWELL**


100%

antimicrobial!

| Order No. |               |               |          | Dim. |   |    |
|-----------|---------------|---------------|----------|------|---|----|
| Black     | Blue          | Grey          | Charcoal | W'   | Х | L' |
| SAQ654    | SAQ655        | SAQ658        | SAQ657   | 2    | Х | 3  |
| SAQ670    | SAQ671        | <b>SAQ674</b> | SAQ673   | 3    | Х | 5  |
| SAQ661    | <b>SAQ662</b> | <b>SAQ664</b> | SAQ663   | 2    | Х | 60 |
| SAQ677    | <b>SAQ678</b> | <b>SAQ680</b> | SAQ679   | 3    | Х | 60 |

### **ENDURABLE NO. 459**

- Longer-wearing two-in-one construction
- PVC sponge has a remarkably durable and abrasion resistant surface
- Created during the manufacturing process, its heat bonded to a comfortable sponge base
- As a dual density anti-fatigue mat, Endurable lasts much longer than similar products, but is very economical
- All edges are safety bevelled
- 1/2" thick
- · Colour: Black



Longer wearing, two-in-one construction!

## **WEARWELL**

## 1-YEAR WARRANT

| Order                    |    | Dim. |         |
|--------------------------|----|------|---------|
| No.                      | W' | х    | L'      |
| NG593                    | 2  | х    | 3       |
| NG596                    | 2  | Х    | 60      |
| NG594                    | 3  | х    | 5       |
| NG595                    | 3  | Х    | 12      |
| NG597                    | 3  | Х    | 60      |
| NG598                    | 4  | х    | 60      |
| CUTS UP TO 60' IN LENGTH |    |      |         |
| NG599                    | 2  | х    | lin.ft. |
| NG600                    | 3  | Х    | lin.ft. |
| NG601                    | 4  | Х    | lin.ft. |

Other lengths available, call for a quote

## SMART TILE-TOP NO. 496

• A SMART solution to standing worker fatigue

WARRANTY Priced like a premium sponge mat, yet wears five times longer


· Economically priced and "Green"


- 100% recycled urethane composite
- Green rating > 80 % recycled
- Comfortable and functional in dry industrial, lab or commercial applications

A smart solution to standing worker fatigue, this mat is economically priced and GREEN.

1-YEAR







|               | Order No.     |               |          |    | )im |          |
|---------------|---------------|---------------|----------|----|-----|----------|
| Black         | Grey          | Blue          | Charcoal | W' | X   | L'       |
| 1/2" THI      | CK            |               |          |    |     |          |
| SBA910        | SBA926        | SBA942        | SBA958   | 2  | х   | 3        |
| SBA911        | <b>SBA927</b> | <b>SBA943</b> | SBA959   | 3  | Х   | 5        |
| SBA912        | <b>SBA928</b> | <b>SBA944</b> | SBA960   | 2  | Х   | 60       |
| SBA913        | <b>SBA929</b> | <b>SBA945</b> | SBA961   | 3  | Х   | 60       |
| <b>SBA915</b> | SBA931        | <b>SBA947</b> | SBA963   | 2  | Х   | lin.ft.* |
| SBA916        | <b>SBA932</b> | <b>SBA948</b> | SBA964   | 3  | Х   | lin.ft.* |
| 7/8" THI      | CK            |               |          |    |     |          |
| <b>SBA918</b> | SBA934        | SBA950        | SBA966   | 2  | Х   | 3        |
| SBA919        | <b>SBA935</b> | SBA951        | SBA967   | 3  | Х   | 5        |
| SBA920        | <b>SBA936</b> | <b>SBA952</b> | SBA968   | 2  | Х   | 60       |
| SBA921        | <b>SBA937</b> | <b>SBA953</b> | SBA969   | 3  | Х   | 60       |
| <b>SBA923</b> | <b>SBA939</b> | <b>SBA955</b> | SBA971   | 2  | Х   | lin.ft.* |
| <b>SBA924</b> | <b>SBA940</b> | SBA956        | SBA972   | 3  | Х   | lin.ft.* |

# COMFORT-KING™ & COMFORT-KING™ SUPREME

 Comfort-King<sup>™</sup> offers optimal cushion and resilience for proper fatigue relief and increased productivity!

 Highly energized Zedlan<sup>™</sup> sponge combines softness, resilience and durability for exceptional relief

 Extra bounce property stimulates muscles and blood flow to reduce fatigue

 Outwears other sponge products by nearly three to one

 Maintains flexibility even in low temperatures


 Supreme 1/2" provides 33% more comfort than standard 3/8"

Ideal for use in all dry work areas!



## TOTAL CONFIDENCE WARRANTY





| Order N    | No.              |    | Dim. |    |
|------------|------------------|----|------|----|
| Black      | Steel Grey       | W' | Х    | L' |
| COMFORT-KI | NG™ 3/8"         |    |      |    |
| NG878      | NG884            | 3  | Х    | 5  |
| NG880      | NG886            | 3  | Х    | 60 |
| COMFORT-KI | NG™ SUPREME 1/2" |    |      |    |
| NH790      | NH789            | 3  | Х    | 5  |
| NH796      | NH795            | 3  | Х    | 60 |

### WEAR-BOND™ TUFF-SPUN®

- Medium-duty anti-fatigue Deck-Top surface for improved abrasion and puncture resistance
- High-density vinyl top with vinyl sponge base
- Impact-absorbing base foam
- 50% greater puncture resistance and five times the abrasion resistance than traditional sponge products
- Lower cost than deck plate sponge products
- 9/16" thick

Applications: Finishing/assembly stations, factories, work stations, cashier's station, pick modules, pharmacies and service counters





| WARRANTY                               | 4             |
|--|---------------|
| WARRAIN'                               | Æ             |
| 407                                    | -             |
|  | -             |
|  | -             |
|  |               |
|  |               |
|  |               |
|  |               |
|  |               |
| 10000000000000000000000000000000000000 | 判             |
| 1 学》,学》,学》,学》                          |               |
| 于经过大型和                                 | = /-          |
| 1 12 12 1                              | =             |
|  | 17            |
|  | $\tilde{I} =$ |
| 1 fi                                   |               |
| -                                      | 作宗            |
|  | - 412         |
|  |               |
|  |               |

1-YEAR

| Order                  |    | Dim. |    |  |
|------------------------|----|------|----|--|
| No.                    | W' | Х    | L' |  |
| BLACK                  |    |      |    |  |
| SAX700                 | 2  | Х    | 3  |  |
| SAX701                 | 3  | Х    | 5  |  |
| SAX702                 | 3  | Х    | 12 |  |
| BLACK W/YELLOW BORDERS |    |      |    |  |
| SAX707                 | 2  | Х    | 3  |  |
| SAX708                 | 3  | Х    | 5  |  |
| SAX709                 | 3  | Х    | 12 |  |

Available in cuts of up to 75' in length

#### ERGO-EASE™

- Premium anti-fatigue mat
- Dual-layer foam hermetically sealed in a rubber shell for extreme wear resistance
- High-quality foam provide softness and comfort for leg and back relief
- Vulcanized commercial grade SBR rubber surface
- Ribbed surface for extra traction and slip resistance
- Can be used in dry and moderately wet (no submersion) environments
- Excellent chemical resistance
- Colour: Black





| Order  |    | Dim | ١.      |
|--------|----|-----|---------|
| No.    | W' | X   | L'      |
| SAQ116 | 2  | Х   | 3       |
| SAQ121 | 3  | Х   | 5       |
| SAQ122 | 3  | Х   | 10      |
| SAQ123 | 2  | Х   | lin.ft. |
| SAQ124 | 3  | Х   | lin.ft. |





#### **TUF SPONGE NO. 451**

- For use in all dry work areas
- An excellent choice for practical and economical comfort
- Blown PVC sponge reduces floor hardness up to 50%
- Can easily be custom cut to fit your work areas
- 3/8" overall thickness with safety rounded edges

|                | Order No.   |               |    | Dim |         |  |
|----------------|-------------|---------------|----|-----|---------|--|
| Black          | Grey        | Black/Yellow  | W' | Х   | L'      |  |
| NB550          | NB551       | SEA533        | 2  | Х   | 3       |  |
| NB565          | NB566       | SEA534        | 3  | Х   | 5       |  |
| <b>SAL427</b>  | SEA535      | SEA536        | 2  | Χ   | 60      |  |
| NB568          | NB569       | <b>SAQ936</b> | 3  | Х   | 60      |  |
| NB574          | NB575       | SEA537        | 4  | Х   | 60      |  |
| <b>CUTS UP</b> | TO 60' IN L | ENGTH         |    |     |         |  |
| JA083          | JA084       | SEA538        | 2  | Х   | lin.ft. |  |
| NG415          | NG418       | SEA539        | 3  | Х   | lin.ft. |  |
| NG416          | JA087       | SEA540        | 4  | Х   | lin.ft. |  |
| JA085          | -           | -             | 6  | Х   | lin.ft. |  |

#### **SS WEARWELL**





#### **ULTRA-TRED ARMORCOTE NO. 440**

#### A URETHANE COATED, PVC SPONGE ANTI-FATIGUE MAT


- Urethane coating gives this anti-fatigue mat extra durability
- PVC sponge with a urethane wear-layer for longer performance
- The double-thick urethane coating offers more abrasion and chemical resistance than comparable sponge products
- A tremendously versatile, yet affordable mat, Ultra Tred is ideal for use in mostly dry applications such as labs and other medium traffic areas
- 3/8" thick with eye-catching yellow safety borders
- · Colour: Black with yellow borders

| Order  |    | Dim. |    |
|--------|----|------|----|
| No.    | W' | X    | L' |
| NB533  | 2  | Х    | 3  |
| NB537  | 3  | Х    | 5  |
| NB534  | 3  | Χ    | 12 |
| SAJ811 | 2  | Χ    | 60 |
| NB538  | 3  | Χ    | 60 |
| NB540  | 4  | Х    | 60 |
|        |    |      |    |

| CUTS UP TO | 60' IN | I LEI | NGTH    |
|------------|--------|-------|---------|
| Order      |        | Dim   |         |
| No.        | W'     | X     | L'      |
| JA080      | 2      | Х     | lin.ft. |
| JA081      | 3      | Χ     | lin.ft. |
| JA082      | 4      | Х     | lin.ft. |

#### **WEARWELL**








## **ORTHOSTAND NO. 454**

- Hollow-domed surface slightly compresses underfoot to encourage subtle changes in posture
- These shifts increase circulation resulting in less fatigue and much more overall comfort
- An economical, dry area, single work area mat, with a resilient natural rubber compound
- Perfect for use at checkout stands, manifest stations, mailing areas and even punch presses
- 1/2" thick
- Green rating > 33% post industrial material
- Colours: Black, black with yellow borders

| Order |    | Dim. |    |
|-------|----|------|----|
| No.   | W' | X    | L' |
| BLACK |    |      |    |
| NB582 | 2  | Х    | 3  |
| NB583 | 3  | Х    | 4  |

| Order     |      | Dim. |    |
|-----------|------|------|----|
| No.       | W'   | х    | L' |
| BLACK/YEI | LLOW |      |    |
| SAL192    | 2    | Х    | 3  |
| SAL193    | 3    | Х    | 4  |

#### **SS WEARWELL**







### **CLEAN ROOM MATS NO. 095**

- Traps impurities in areas that require dirt and dust control
- Perfect for outside controlled manufacturing areas, clean rooms, or labs, also keeps dirt from tracking into office areas
- The tacky surface efficiently pulls dirt and dust off shoe soles before it can contaminate a clean or sterile room
- Effective and easy to use, each mat has 30 or 60 layers of tough film once the top layer is contaminated, simply pull it off and discard
- Use on tile, low-profile carpet or concrete surfaces
- Colours: Blue or white
- Sold per case of 4



| 30 Layers 60 Layers |        | 60 Layers |    | Dim. |    |  |
|---------------------|--------|-----------|----|------|----|--|
| White               | Blue   | White     | W" | х    | L" |  |
| SEB153              | SEB152 | SEB162    | 18 | Х    | 36 |  |
| SEB155              | SEB154 | SEB163    | 18 | Х    | 45 |  |
| <b>SEB159</b>       | SEB158 | -         | 24 | Х    | 36 |  |
| <b>SEB157</b>       | SEB156 | SEB164    | 24 | Х    | 45 |  |
| <b>SEB161</b>       | SEB160 | -         | 36 | Х    | 45 |  |



## SANITIZING FOOTBATH MATS NO. 222


- Designed to decontaminate and disinfect footwear, this mat keeps hygienic areas free of debris and germs
- Especially effective in food processing facilities, the mat is simply filled with a diluted chlorine or quaternary solution
- As employees step on the mat, their shoe treads are immersed in the disinfectant solution while the pliable rubber scrapers dislodge contaminants
- For complete decontamination, shoe soles must be immersed for one minute
- Standard mat holds up to 1 gallon
- Tall wall (2 1/2" walls) holds up to 5.5 gallons, the liquid is at least
   2" high and can disinfect well past the sole of the shoe or boot



### **WEARWELL**

| Order  |    | Dim. |    |                        | Absorption  |
|--------|----|------|----|------------------------|-------------|
| No.    | W" | X    | L" | Colour                 | Capacity    |
| SAL651 | 24 | х    | 32 | Black                  | 1 gallon    |
| SAQ090 | 32 | Х    | 39 | Black                  | 5.5 gallons |
| SEA554 | 32 | Х    | 39 | Black w/Yellow Borders | 5.5 gallons |





#### **COMFORT KING™ ANTI-MICROBIAL**

- Offers optimal cushion and resilience while inhibiting bacteria and germ growth
- Anti-microbial additive inhibits the growth of harmful micro-organisms
- Highly energized Zedlan™ sponge combines softness, resilience and durability for exceptional relief
- Outwears other sponge products by nearly three to one
- · Maintains flexibility even in low temperatures
- Ideal for dry environments such as hospitals, nursing homes, daycare facilities, laboratories etc.

| Order  |    | Dim. |    |
|--------|----|------|----|
| No.    | W' | х    | L' |
| SAM328 | 2  | Х    | 3  |
| SAM330 | 3  | Х    | 5  |
| SAM333 | 2  | Х    | 60 |
| SAM334 | 3  | Х    | 60 |
| SAM335 | 4  | Х    | 60 |

| Order         | Dim. |   |          |  |  | Dim. |  |  |
|---------------|------|---|----------|--|--|------|--|--|
| No.           | W'   | X | L'       |  |  |      |  |  |
| SAM336        | 6    | Х | 60       |  |  |      |  |  |
| <b>SAM337</b> | 2    | Х | lin.ft.* |  |  |      |  |  |
| SAM338        | 3    | Х | lin.ft.* |  |  |      |  |  |
| SAM339        | 4    | Х | lin.ft.* |  |  |      |  |  |
| SAM340        | 6    | Х | lin.ft.* |  |  |      |  |  |

\*Cuts up to 60' in length







#### **WORKRITE NO. 474**

- · Perfect for wet commercial or industrial areas
- General purpose, natural rubber compound for use around water and non-caustic agents
- Lightweight design eases the strain of cleaning, yet keeps employees comfortable
- Functional drainage design
- Molded bevelled edges for easy access
- 1/2" thick
- · Colour: Black

Economical anti-fatigue mat provides both safety & comfort!

#### **WEARWELL**

| Order Dim. |    | Dim. |    | Wt.  |  |
|------------|----|------|----|------|--|
| No.        | W' | х    | L' | lbs. |  |
| NB607      | 3  | Х    | 5  | 25   |  |
| NG013      | 3  | Х    | 10 | 50   |  |
| NG014      | 3  | Х    | 20 | 100  |  |



### **MODULAR WORKSAFE® LIGHT NO. 472**

#### LIGHTWEIGHT, MODULAR ANTI-FATIGUE MATTING

- Creates an ergonomic "Floor above a Floor"
- 3' x 3' single workstation sections use a hidden interlocking system that requires no additional bevels or attachment devices
- Perfect for high maintenance areas, it's lightweight and easy to clean
- Overall thickness of 1/2" with safety rounded edges and excellent drainage
- Available in two compounds: General purpose natural rubber (green rating > 20% post industrial material, and a Grease Proof – 50% nitrile rubber (for use around greases, chemicals and caustic agents)
- Colour: Black



## **WEARWELL**

| Order |                 |    | Dim. |    | Wt.  |
|-------|-----------------|----|------|----|------|
| No.   | Description     | W' | Х    | L' | lbs. |
| NC823 | General Purpose | 3  | Х    | 3  | 11   |
| NC824 | Grease-Proof    | 3  | Х    | 3  | 11   |
|       |                 |    |      |    |      |

Exceptionally comfortable modular design allows you to dimension the mat to your exact requirements!



#### GRADE A® NO. 482


- Anti-fatigue mat specifically for food production plants
- 100% anti-microbial nitrile rubber withstands animal fats, fish and vegetable oils
- Passes the NSF anti-microbial test ASTM G21-96 (2002)
- Built-in handles
- No areas where food particles can collect
- Substantial underside knobs increase comfort
- Increases traction when greasy and wet
- 1/2" thick
- Colour: Terra Cotta

Substantial underside knobs are 1/4" high

## **WEARWELL**

| Order Dim.            |
|-----------------------|
| No. W" x L"           |
| SAN571 30 x 36        |
| <b>SAN572</b> 30 x 60 |

Solid underside design



Hygienić porthole design

Accepted for use in Canadian food processing facilities





### **WELDSAFE® NO. 447**

#### **PERFORMANCE: BEST**


- Dramatically reduces fatigue while withstanding the challenges of welding environments
- Specially formulated to repel sparks and hot metal shards, the thick rubber surface has a melt point of over 500°F
- The super resilient Nitricell® sponge base is a nitrile rubber composite that offers unparalleled comfort
- All edges are safety bevelled
- 3/8" thick
- Green rating > 33% post industrial material
- Colour: Black

## 3-YEAR WARRANTY

3/8"

### **WEARWELL**

Thicker Rubber surface



Nitricell® sponge base



| Order                    |    |   |         |
|--------------------------|----|---|---------|
| No.                      | W' | х | L'      |
| NG181                    | 2  | х | 3       |
| NG182                    | 3  | Х | 5       |
| CUTS UP TO 75' IN LENGTH |    |   |         |
| SAL188                   | 2  | х | lin.ft. |
| NG184                    | 3  | Х | lin.ft. |
| SAL189                   | 4  | Х | lin.ft. |

Other lengths available, call for a quote.


## NON-CONDUCTIVE CORRUGATED SWITCHBOARD NO. 702 & DIAMOND PLATE SWITCHBOARD NO. 701

- High-performance non-conductive matting conforms to ANSI/ASTM D-178-01 Type II, Class 2
- Designed to protect personnel in areas with dangerous high-voltage equipment, these mats can insulate against as much as 30000 volts of electricity
- Available in two surface designs:
   Diamond-plate is easily cleaned
   Corrugated for extra traction
- 1/4" thick

Passes U.S. Department of Labour Mine Safety and Health Administration—Title 30, Code of Regulations 18.65 Flammability Rating for products taken into mines.

Type II— Refers to the material compound-a virgin PVC resistant to chemical and other spills, ozone and UV.





## 1-YEAR WARRANTY

| No. 702    |          |      |         |
|------------|----------|------|---------|
| Order      |          | Dim. |         |
| No.        | W'       | х    | Ľ'      |
| CORRUGATE  | D        |      |         |
| SAL242     | 2        | Х    | 75      |
| NB657      | 3        | Х    | 75      |
| NB659      | 4        | Х    | 75      |
| CUTS UP TO | 75' IN L | ENG  | TH      |
| SAL241     | 2        | Х    | lin.ft. |
| NB658      | 3        | Х    | lin.ft. |
| NR660      | 4        | X    | lin ft  |

| No. 701      |         |      |         |
|--------------|---------|------|---------|
| Order        |         | Dim. |         |
| No.          | W'      | X    | Ľ'      |
| DIAMOND-PLA  | ATE     |      |         |
| SAL236       | 2       | Х    | 75      |
| SAL238       | 3       | Х    | 75      |
| SAL240       | 4       | Х    | 75      |
| CUTS UP TO 7 | 5' IN L | ENG  | TH      |
| SAL235       | 2       | Х    | lin.ft. |
| SAL237       | 3       | Х    | lin.ft. |
| SAL239       | 4       | Х    | lin.ft. |

### ELECTRICALLY CONDUCTIVE ANTI-FATIGUE NO. 786DP

- A very popular static control solution in manufacturing facilities
- · Dramatically reduces the percentage of defective product and employee complaints
- · Quickly drains static electricity from workers and effectively protects sensitive equipment and products from damage
- Effectively prevents the incidence of sparks caused by static discharge
- Designed to dramatically reduce fatigue, the Nitricell® sponge base is a nitrile rubber composite designed for comfort and long-term performance
- Available in a diamond-plate surface (RTG = 5 x 10<sup>5</sup> to 1 x 10<sup>7</sup> ohms)
- 9/16" thick
- This mat must be grounded and employees must either wear heel grounders or conductive shoes

#### **SWEARWELL**

| Order   |                         |        | Dim  | ١.      | Wt.  |
|---------|-------------------------|--------|------|---------|------|
| No.     | Description             | W'     | Х    | L'      | lbs. |
| SAL243  | Smooth Surface          | 2      | Х    | 3       | 8.1  |
| NB692   | Diamond-Plate Surface   | 3      | Х    | 5       | 23   |
| CUTS UP | TO 75' IN LENGTH        |        |      |         |      |
| NB693   | Diamond-Plate Surface   | 3      | Х    | lin.ft. | 5    |
| SAJ574  | 15' L Ground Wire (Solo | d Sepa | rate | ly) 1   |      |



## STATIC DISSIPATIVE ANTI-FATIGUE NO. 791

QUICKLY DRAINS STATIC ELECTRICITY FROM WORKERS

- This mat has a metal scrim embedded in the vinyl surface to ensure speedy and effective dissipation of static electricity
- The Nitricell® sponge base is a nitrile rubber composite designed for employee comfort and productivity
- Ideal for manufacturing and commercial areas where static electricity can pose a problem, this mat has an RTG =  $1 \times 10^7$  to  $5 \times 10^8$  ohms
- It must be grounded and employees must either wear heel grounders (SAL252) or conductive shoes
- 1/2" thick

#### **WEARWELL**

| Order        |             | Dim |            |            |         |  |
|--------------|-------------|-----|------------|------------|---------|--|
| No.          | W'          | Х   | L'         |            |         |  |
| NH534        | 2           | Х   | 3          |            |         |  |
| NH535        | 3           | Х   | 5          |            |         |  |
| CUTS UP TO 7 | 5' IN LENGT | Ή   |            |            |         |  |
| NB694        | 3           | Х   | lin.ft.    |            |         |  |
| NB695        | 4           | Х   | lin.ft.    |            |         |  |
| SAJ574       | 15'         | L G | round Wire | (Sold Sepa | rately) |  |

Grounding snap is attached to lower left hand corner of each mat



### HEEL GROUNDER NO. 793HG

- The heel grounder allows static electricity to pass from the worker to the ESD matting or flooring
- One size fits all and the velcro loop allows for easy attachment
- Allow the fabric strip to touch the workers skin for best performance
- One megohm resistor
- 0.060" thick

Order No. SAL252

## **W**WEARWELL

## REQUIRED ACCESSORIES FOR ESD MATTING

15' GROUND CORD NO. 793.15

- Use this cord to connect all ESD tabletop and floor mats to a building ground
- The solderless terminal can be connected to an electrical outlet by using the screw in the outlet cover
- The molded-in snap fastener has an integral one megohm resistor and conforms to 10 mm snaps

Order No. SAJ574





### **CHOOSING THE RIGHT MAT**

THERE ARE THREE TYPES OF MATTING TO CONSIDER.
TO SELECT THE RIGHT TYPE FOR YOU, WE RECOMMEND THE FOLLOWING STEPS:

- 1. Identify the type of area where you wish to install the carpet, taking into account the amount of traffic it will experience. (ex: heavy traffic vs. light traffic)
- 2. Refer to the collection of products in the following pages and locate the right fit for you. We've categorized each mat to correspond to one of the four traffic categories, colour coded for your convenience
- 3. Choose a scraper, a wiper/scraper and a wiper mat.

  Note: For best results, use three types of mats in the following combination (ex: Upfront Scraper, Super Soaker and Proluxe)

#### 1-SCRAPER

- · Exterior usage or between two doors
- Aggressive scraper surface, which will capture the majority of dirt from the soles of shoes
- Does not absorb moisture, which facilitates maintenance

#### 2-WIPER/SCRAPER

- Interior usage or between two doors
- Irregular surface which enables trapping moderate dirt that was not captured at the scraper level
- Moderately retains water and moisture that may later evaporate or be extracted at a later time

#### 3-WIPER

- Interior usage
- Plays a major role in the retention of water and fine dust
- Minimizes the risk of slipping and falling

| Light   | Light-Medium   | Medium-Heavy  | Heavy  |
|---|--|---|--|
| Traffic   | Traffic  | Traffic   | Traffic  |
| Less than 125 foot traffic per day  Small business Boutiques Side Entrance Etc. | Between 125 & 500<br>foot traffic per day<br>Office building<br>Small retail store<br>Bank/Postal Service<br>Car Dealership<br>Motel & Inn<br>Etc. | Up to 1500 foot traffic per day  Convenience Store Restaurant Hotel Theatre Museum Convention Centre Etc. | Over 1500 foot traffic per day  University Airport Hospital Large retail store Shopping Mall School Etc. |

#### **DID YOU KNOW?**

The proper use of entrance mats is recognized by the Green Building Council of Canada, under LEED® certification system (Leadership in Energy and Environmental Design), visioning a transformed built environment leading to a sustainable future. Some MatTech products can contribute to obtaining two credits:

- 1 Credit\*: "Permanently use the entrance matting system to capture dirt, particles etc. from entering the building at all high volume entrances"
- 1 Credit\*\*: Use material with recycled content in order that the sum [...] constitutes at least 7.5% of the total value of the material in the project. For more information, visit the website: www.cagbc.org
- \*EQ Credit 5 requirements, Green Building Rating System v1.0
- \*\*MR Credit 4.1 requirement, Green Building Rating System v1.0



## **Entrance Matting**

### HEAVY-DUTY MULTI-GUARD NO. 220

- High performance outdoor entrance mat
- Thousands of scraping fingers effectively remove pounds of dirt from sight and hold it between cleanings
- Works even during the worst weather conditions
- 1/2" overall thickness with safety bevelled edges
- Colour: Black

Uses: Heavily trafficked outdoor entrances

1-YEAR WARRANTY

Exceptional dirt trapping qualities solve the problem of







damaging grime & moisture tracking!

| Order |    | Dim. |    | Wt.  |
|-------|----|------|----|------|
| No.   | W" | x    | L" | lbs. |
| NB206 | 24 | Х    | 32 | 8    |
| NB207 | 28 | Х    | 46 | 15   |
| NB208 | 32 | X    | 39 | 15   |
| NG588 | 36 | X    | 60 | 31   |
| NB209 | 36 | Х    | 72 | 35   |

#### WIPER/SCRAPERS - CROSS-OVER™

- Enhance the appearance of your entrance with the rich look of a loop-pile tufted mat
- Now 30% heavier than before for better performance
- Attractive two tone colours and resilient construction resist fading and crushing
- Non-absorbent, abrasive surface scrapes debris and moisture from footwear while sturdy olefin fibres start the drying process
- Other sizes and colours available





| Ord   | er No.   | Din | nensi | ons     |  |
|-------|----------|-----|-------|---------|--|
| Brown | Charcoal | W'  | Х     | L'      |  |
| NG735 | NG743    | 3   | Х     | 5       |  |
| NG738 | NG746    | 4   | Х     | 6       |  |
| NG741 | NG749    | 3'  | Х     | lin.ft. |  |

### **UPFRONT SCRAPER MAT NO. 224**

 Popular and classic design effectively scrapes dirt, snow and rain off shoes, containing it outside


 Pliable and durable rubber compound is highly resistant to harsh outside elements
 Low profile accommodates tight doorways

Easy to clean, simply hose it down or shake it off and it's ready to go
5/16" thick

 Also available in a quick-dry, vented version that features an open slot design to facilitate drainage

• Colour: Black

1-YEAR WARRANTY





#### **WEARWELL**

| Order |             |    | Dim. |    |  |
|-------|-------------|----|------|----|--|
| No.   | Description | W' | x    | L' |  |
| JA187 | Solid       | 3  | Х    | 5  |  |
| JA911 | w/Slots     | 3  | Х    | 5  |  |

## SUPER-SOAKER™ WAFFLE PATTERN

Well respected, Super-Soaker™ is the most reliable wiper/scraper for demanding environments!

- Non-skid nib backing will effectively grip mat to the floor
- Crush-proof waffle pattern will maintain appearance and performance, extending mat's life
- Elevated construction will scrape shoes and hold dirt beneath shoe level, while wiping moisture
- Thickness: 3/8"
- Other colours and sizes available








|               | Order No.     |               |    | Dim |     |  |
|---------------|---------------|---------------|----|-----|-----|--|
| Charcoal      | Walnut        | Grey          | W" | X   | L"  |  |
| NG869         | <b>SEB895</b> | NG872         | 35 | Х   | 58  |  |
| <b>SEB896</b> | <b>SEB897</b> | <b>SEB898</b> | 35 | Х   | 116 |  |
| NG870         | <b>SEB899</b> | NG873         | 45 | Х   | 68  |  |
| SEB900        | SEB901        | SEB902        | 45 | Х   | 119 |  |

### **CHEVRON**<sup>TM</sup>


- The decorative Chevron V pattern enables this mat to perform well in multi-directional traffic areas
- The premium vinyl backing guarantees against water penetration
- The 100% polypropylene fibres are resistant to ice melts, salts, chlorine, petroleum products, caustic soda as well as mould and mildew
- Recommended for low to moderate traffic areas
- 5/16" thick



Attractive & durable multi-directional wiper/scraper needle punch mat!







### WIPERS - WALK-A-WAYTM

- Enhance the appearance of your entrance with the rich look of a loop-pile tufted mat
- Now 35% heavier than before for better performance
- Attractive two tone colours and resilient construction resist fading and crushing
- Dense, fast drying fibres absorb heavy moisture and trap fine dirt particles
- Other sizes and colours available



| Ord   | ler No.  |    | Dim. |         |
|-------|----------|----|------|---------|
| Brown | Charcoal | W' | х    | L'      |
| NG759 | NG767    | 3  | Х    | 5       |
| NG761 | NG769    | 3  | X    | 60      |
| NG762 | NG770    | 4  | X    | 6       |
| NG764 | NG772    | 4  | X    | 60      |
| NG765 | NG773    | 3  | Х    | lin.ft. |





#### **NEEDLE-RIB™**

- 100% polypropylene needle punch, surface-bonded to a vinyl backing
- Ribbed polypropylene fibre pattern that traps moisture
- · Gently brushes debris from shoes
- 5/16" thick



| Orde  | r No.    |    | Dim. |         |  |
|-------|----------|----|------|---------|--|
| Brown | Charcoal | W' | Х    | Ľ'      |  |
| NG822 | NG832    | 3  | Х    | 4       |  |
| NG823 | NG833    | 3  | Х    | 5       |  |
| NG827 | NG837    | 4  | Х    | 6       |  |
| NG830 | NG840    | 3  | Х    | lin.ft. |  |
| NG831 | NG841    | 4  | Χ    | lin.ft. |  |

The traditional and reliable wiper/scraper needle punch mat for low traffic areas!







#### **PROLUXETM**

- Removes excess water and dirt particles from footwear
- Moisture and dust is absorbed into the bottom of the mat, leaving the top mat surface relatively dry
- Water and dirt particles stay on the mat not on expensive floors and carpets
- 5/16" thick




| Orde     | er No.       |    | Dim. |         |  |
|----------|--------------|----|------|---------|--|
| Charcoal | Pebble Brown | W' | X    | Ľ       |  |
| NG783    | NG801        | 3  | Х    | 5       |  |
| NG786    | NG804        | 4  | Х    | 8       |  |
| NG787    | NG805        | 3  | Х    | 60      |  |
| NG789    | NG807        | 3  | Х    | lin.ft. |  |
| NG790    | NG808        | 4  | X    | lin.ft. |  |

100% olefin super drying mat!







## **Entrance Matting**

#### **ECOPLUSTM**

- 100% recycled surface, 20% recycled backing
- Non-skid nib backing will effectively grip mat to the floor
- Crush-proof "V" pattern will maintain appearance and performance
- Elevated construction will scrape shoes and hold dirt beneath shoe level, while wiping moisture
- colours, use in combination with our ECO-STEP<sup>TM</sup> wiper mat • For best results and similar












| Orde     | er No.        |    | Dim. |    |  |
|----------|---------------|----|------|----|--|
| Charcoal | Walnut        | W' | X    | L' |  |
| SAX726   | SAX731        | 3  | Х    | 5  |  |
| SAX727   | <b>SAX732</b> | 3  | Х    | 10 |  |
| SAX728   | SAX733        | 4  | Х    | 6  |  |
| SAX729   | SAX734        | 4  | Х    | 10 |  |

## ECO-STEP™

- Retains liquid and fine dirt
- Quality plush surface dries quickly
- Premium vinyl backing with natural organic resin blend prevents water from damaging floors
- For best results and similar colours, use in combinationwith our ECOPLUS™ wiper/scraper mat









| Orde     | er No. |    | Dim. |    |  |
|----------|--------|----|------|----|--|
| Charcoal | Walnut | W' | X    | L' |  |
| SAX714   | SAX720 | 3  | Х    | 5  |  |
| SAX715   | SAX721 | 3  | Х    | 10 |  |
| SAX717   | SAX723 | 4  | Х    | 6  |  |
| SAX718   | SAX724 | 4  | X    | 10 |  |

## STANDARD CORRUGATED VINYL NO. 381

#### THE MOST POPULAR RUNNER MAT!

- Protects floors from foot traffic or special events
- Adds traction where needed
- Reduces cleaning costs
- Flexible, yet durable vinyl compound easily rolls up after use
- 1/8" thick
- Colour: Black

The all-purpose runner that makes floors safer to walk on!

| Order |    | Dim. |         |
|-------|----|------|---------|
| No.   | W' | х    | L'      |
| NB374 | 3  | Х    | 105     |
| NB376 | 4  | Х    | 105     |
| NB375 | 3  | Х    | lin.ft. |
| NB377 | 4  | Х    | lin.ft. |






#### 1/8" RUBBER RUNNER

- Flexibility in cold weather
- Long wearing, superior abrasion resistance and comfort
- Does not curl up on the edges
- · Absorbs noise from hard floor
- 1/8" thick
- Colour: Black

Applications: All entrances.





| Order       | Dim. |           |        |  |  |  |
|-------------|------|-----------|--------|--|--|--|
| No.         | W'   | W' x L'   |        |  |  |  |
| FINE RIBBED |      |           |        |  |  |  |
| JA121       | 2    | Х         | 75     |  |  |  |
| JA122       | 3    | Х         | 75     |  |  |  |
| JA123       | 4    | Х         | 75     |  |  |  |
| JA124       | 2    | хI        | in.ft. |  |  |  |
| JA125       | 3    | x li      | n.ft   |  |  |  |
| JA126       | 4    | x lin.ft. |        |  |  |  |

| Order    |     | Dim.      |  |  |  |  |  |
|----------|-----|-----------|--|--|--|--|--|
| No.      | W'  | W' x L'   |  |  |  |  |  |
| WIDE RIB | BED |           |  |  |  |  |  |
| NI363    | 2   | x 75      |  |  |  |  |  |
| NI304    | 3   | x 75      |  |  |  |  |  |
| NI305    | 4   | x 75      |  |  |  |  |  |
| NI364    | 2   | x lin.ft. |  |  |  |  |  |
| NI306    | 3   | x lin.ft. |  |  |  |  |  |
| NI307    | 4   | x lin.ft. |  |  |  |  |  |

### 1/4" RUBBER RUNNER

- Flexibility in cold weather
- Long wearing, superior abrasion resistance and comfort
- Does not curl up on the edges
- · Absorbs noise from hard floor
- 1/4" thick
- Colour: Black




| Order |    | Dim. |         |
|-------|----|------|---------|
| No.   | W' | х    | L'      |
| JA684 | 3  | Х    | 75      |
| JA686 | 3  | Х    | lin.ft. |

#### TRAXION GRIP NO. TIP1

- Modular interlocking 12" x 12" tile mat
- Wraparound edging prevents tripping
- 529 holes per tile assures excellent drainage of fluids
- Raised grippers on tiles guard against slippage
- 1/2" PVC is resistant to chemicals, oils, grease and animal fat
- · Resistant to mould and mildew
- Fire resistant

Applications: Wet or dry work areas.

Modular design allows you to size the mat to your exact specifications!



#### COMFORT TRED NO. TIL2

- Molded from durable PVC
- Raised ridges scrape off dirt
- Drainage holes allow dirt to fall through tiles
- Resistant to mould and mildew
- 12" x 12" tiles with optional beveled wraparound edges

**Applications**: Indoor entrances and shower areas.





Modular design allows you to dimension the mat to your exact specifications!

| TILES | WRAPAROUND E | DGES   |
|-------|--------------|--------|
| Order | Order        |        |
| No.   | No.          | Colour |
| NB378 | NB386        | Black  |
| NB380 | NB388        | Grey   |
| NB383 | NB391        | Tan    |
| NC822 | NG055        | Navy   |

## **Entrance Matting**

## **OUTFRONT REVERSIBLE** SCRAPER NO. 227

 OutFront Reversible Scraper redefines what an outdoor mat can do

• Totally reversible, it's easily flipped over to accommodate all weather conditions

• One side features rows of flexible scrapers alternating with quick-dry drainage ports for a "brush and release" effect

• The other side features clusters of stiff ridges designed to scrape heavier debris and packed snow off outsoles


• 7/16" thick with an evenly tapered border on all four sides


· Accommodate a single, or double entryway

• Colour: Black

1-YEAR WARRANTY







Х

24

Grey

#### **WEARWELL**

| Order  | Dim. |   |    |  |
|--------|------|---|----|--|
| No.    | W'   | X | L' |  |
| SAQ318 | 3    | х | 6  |  |

#### **MUD CHUCKER NO. 229**

15/16" THICK MOBILE SHOE SCRAPER MAT

• A portable shoe scraper that effectively removes dirt, snow, grass clippings or any other muck off the sides and bottoms of boots or shoes

• The pliable rubber fingertips scrape both the sides and bottom of footwear

• Small enough to use in tight spaces or as a mobile entrance mat for workers who toil in muddy areas and then travel to the next location

• Recessed holes allow the Mud Chucker to be bolted in place

• Easy to clean, simply shake to remove the dirt or spray off with a hose

• 1" thick at front edge; 2 3/8" on sides

· Colour: Black

| Order  | D      | imensior | ıs     | Wt.  |  |
|--------|--------|----------|--------|------|--|
| No.    | W"     | X        | L"     | lbs. |  |
| SAL652 | 12 3/8 | х        | 15 1/4 | 4.5  |  |



## **BOOT-BOY® INDUSTRIAL** FOOTWEAR CLEANERS

• Constructed of 14-gauge hot rolled steel

• Nylon brush is long lasting and easily replaceable

• Brush can be used wet with water, degreasers in pan or dry

- Plugs into any standard outlet
- 1/3 HP ball bearing motor
- · Powder coated finished in red
- CSA approved

Order No. NI593





#### **BOOT 'N SHOE BRUSHES**

14

- Brushes thoroughly clean all boot and shoe surfaces
- Flip the brushes up to reveal a heavy duty sole scraper
- Anchor it in concrete or secure the solid metal frame with a single foot while cleaning the other
- · Shipped completely assembled
- Polypropylene stiff bristle

**BOOT TRAYS** 

**SAS411** 

• Durable and flexible plastic construction boot tray traps water, mud and dirt

· High ribbed surface protects shoes



| Order |                          |        | Block Dimensions |        |   |       |
|-------|--------------------------|--------|------------------|--------|---|-------|
| No.   | Description              | L"     | X                | W"     | X | H"    |
| NH576 | Boot 'N Shoe Brush, Blue | 14 3/4 | Х                | 16 1/2 | Х | 7     |
| NH577 | Replacement Brush, Blue  | 10     | Х                | 4 1/2  | Х | 3 1/2 |